




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : <b>G06K 9/62</b>		<b>A1</b>	(11) International Publication Number: <b>WO 00/13136</b>
			(43) International Publication Date: 9 March 2000 (09.03.00)
(21) International Application Number: PCT/US99/19723 (22) International Filing Date: 31 August 1999 (31.08.99) (30) Priority Data: 60/098,687 31 August 1998 (31.08.98) US (71) Applicant (for all designated States except US): DIGITAL VIDEO EXPRESS, L.P. [US/US]; 580 Herndon Parkway, Herndon, VA 20170 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): IU, Siu-Leong [PT/US]; Apartment 305, 1211 Garbo Way, San Jose, CA 95117 (US). DAVIS, Malcom [US/US]; Apartment 4, 10280 SE 6th Street, Bellevue, WA 98004-6188 (US). LUO, Hui [PT/US]; 100 Schultz Drive, Red Bank, NJ 07701 (US). LIN, Yun-Ting [PT/US]; 345 Scarborough Road, Briarcliff Manor, NY 10510 (US). MERCIER, Guillaume [FR/US]; Apartment 437, 1504 Lincoln Way, McLean, VA 22102 (US). BUGWADIA, Kobad [IN/US]; 555 E. Washington Avenue, #1202, Sunnyvale, CA 94086 (US). (74) Agents: DEVINSKY, Paul et al.; McDermott, Will & Emery, 600 13th Street, N.W., Washington, DC 20005-3096 (US).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>	

(54) Title: WATERMARKING SYSTEM AND METHODOLOGY FOR DIGITAL MULTIMEDIA CONTENT



## (57) Abstract

An open digital watermark system and methodology having various features for unifying watermark production and processing among diverse user multimedia terminals (112), such as set top box, that may be OPIMA compliant. In accordance with specific aspects, intentional image warping is employed to combat pirating, the analog video channel used to download programming, packet signature implemented for watermark insertion by pixel replacement and use of the data stream made to reduce local data processing and storage.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## Watermarking System and Methodology for Digital Multimedia Content

### Technical Field

5 This invention relates generally to data protection, and more particularly to aspects of a novel digital watermark system and methodology for multimedia content, such as audio, video, text, still images, computer graphics, and software.

### Background Art

10 A watermark is an imperceptible or at least difficult to perceive signal embedded into multimedia content such as audio, video, text, still images, computer graphics, or software. The watermark conveys some useful information without disturbing or degrading the presentation of the content in a way that is noticeable or objectionable. Watermarks have been used for the purpose of protecting the property rights of content providers, e.g., by helping to identify the rightful owner of the content. In this case, it should be possible reliably to retrieve the  
15 watermark even from content that has been significantly modified or degraded by various causes. The watermark should be resistant to intentional or unintentional removal, counterfeiting, or other tampering without substantial degradation to the content, significantly reducing its commercial value. A watermark should survive innocent processing like compression, decompression, analog to digital and digital to analog conversion, and format  
20 conversion (e.g., converting video from NTSC to PAL). The watermark should defy a deliberate attack by a pirate using common signal processing operations. In addition, it must be difficult to counterfeit a watermark; otherwise, watermarks might not be useful, for example, in resolving multiple claims of ownership.

Watermarking technology is divided into three broad categories with different objectives,  
25 namely, tracing, copy protection and proof of ownership (copyright protection). Tracing identifies users that sell or give away illegal copies of protected content. Copy protection is implemented to prevent coping (at least, by compliant recorders) of content that contains a watermark denoting that the content should not be copied. Proof of ownership invalidates claims of ownership by anyone other than the legitimate owner of a copyrighted work.

30 To help trace the illegal redistribution of multimedia content, a watermark can be inserted into the content that contains information, which identifies the source of the copy. This watermark can include information such as the user identification number (e.g., from a smartcard), the serial number of the terminal, the serial number of the content, and the date and

time the content was presented or copied. Since the watermark is different for every terminal and every user of the terminal, it must be inserted by the terminal and similar devices (at least, for broadcasted content such as pay-per-view and video on demand). This type of watermark may be recovered off-line by the content provider, service provider, or law enforcement officials.

To provide proof of ownership, the content provider or service provider embeds a watermark into the multimedia content prior to public distribution. The watermark may be embedded into uncompressed or compressed versions of the content (or both). A properly constructed watermark unambiguously identifies the owner of the content. Later, if multiple claims of ownership need to be resolved, only the rightful owner of the content can recover the watermark from each copy of the content claimed to be an original.

Currently proposed watermarking techniques are proprietary and mutually incompatible. A standardized and unified approach would benefit the consumer by allowing interoperability among different content providers, service providers, and terminal equipment. Consistent and dependable methods for content protection also benefit the consumer since it gives content providers and service providers more incentive to provide content. This invention attempts to reap these benefits by placing a wide variety of watermarking techniques into a unified and standardized framework that is incorporated into a terminal compliant, for example, with the currently proposed Open Platform Initiative for Multimedia Access (OPIMA), the framework for which is described in the called for proposals by the OPIMA, dated July 24, 1998. In accord with the OPIMA philosophy, the proposed watermark standard is open and expandable. Standardization and openness are required because proprietary systems discourage the consumer due to a lack of interoperability. For example, deploying a video recorder that will only record content containing a "copying is allowed" watermark is worthwhile only if it can retrieve watermarks inserted by playback devices produced by many manufacturers. In addition, standardization and openness ensure that compliant devices have at least the minimum capabilities required to support the necessary functionalities (including watermarking). Expandability is needed because experience clearly indicates that technology advances rapidly and, in particular, security technology does not remain secure for very long whereas consumer electronics devices may remain in service for more than a decade. Also, new types of content and new technologies, not yet imagined, must be secure and protected.

Application serial number 09/092,898, filed on June 8, 1998, assigned to the assignee of the present invention and incorporated herein by reference, describes a digital watermark system implementing novel "running marks" embedded into "message holes" in a bitstream bearing information, such as audio, video, still pictures, software, etc., for which there is a proprietary  
5 interest to be protected. The message holes are in locations in the bitstream, strategically positioned to be impossible or difficult to observe in a frame (when the bitstream comprises a video signal). In an MPEG environment, the message holes are macroblocks each capable of storing one or more carrier bits of data. The running marks are injected into the message hole locations of the bitstream at the time a medium, such as a DVD, is played. The data represented  
10 by the running marks identify the serial numbers of the player and DVD, and the time of play. This information is decoded by an enforcement institution that will play back the contents of an unauthorized copy of the DVD to extract the running marks to be used to trace to the copyist.

To make the extraction process more difficult, an unauthorized copyist (pirate) may combine video outputs from a number of video players when a copy is made, so that the running  
15 mark information associated with any one player will not be easily read unambiguously. The copending application describes methodology using code division multiple access coding (CDMA) to detect the running marks associated with each single player among running marks associated with all the players used. Each player in this methodology encodes its running mark data using a different low correlation waveform. The example described in the application  
20 implements a set of Hadmard-Walsh (HW) waveforms because they are mutually orthogonal and easily generated. During decoding by the institution to extract the running mark information, bits are recovered by performing correlation (inner products) between the received waveform and reference waveforms to decode the running marks and provide source-of-copying information. Since correlation among these waveforms is low, inner product processing extracts  
25 the running mark bits correctly in a field of received waveforms from multiple players. The waveform adopted by a player is selected randomly at runtime from a finite set waveforms, to avoid the situation, although rare, where a pirate may use multiple players having the same waveform to make a copy. To additionally make the waveforms more difficult for the pirate to determine, the described methodology includes waveform value scrambling and uses more than  
30 one waveform in a bitstream. To preserve the orthogonal property, and reduce the effect of burst error, the waveforms are permuted among different columns first and then among different rows. Storage of the CDMA waveform values (this may be incorporated in a separate security chip),

even on a column basis, requires a considerable amount of memory. Placing the storage off chip is complicated, and security in that event is compromised.

Despite that the described system and methodology is an effective means to thwart piracy, an even greater level of security is preferred. No security methodology can be made absolutely  
5 immune from defeat by reverse engineering on the part of a committed pirate. However, it is desirable at least to maximize the amount of time it will require a pirate to invade security so that valuable proprietary material, such as a currently popular movie, is not misappropriated early in its commercial lifetime when it is most valuable.

It is also desirable to utilize the bandwidth of the running mark system, described in the  
10 copending application, more efficiently and with greater versatility, to enable the system more easily to accommodate changes in software programming and to simplify running mark housekeeping functions.

It is particularly desirable to formulate a variety of watermarking techniques into a unified and standardized framework that may be incorporated into, for example, an OPIMA compliant  
15 terminal.

#### **Disclosure of the Invention**

The above and other objectives and advantages are achieved, at least in part, by a novel system and methodology for processing a video bitstream where multiple (N) copies have been combined by a pirate from N players, for making it difficult to extract the running mark data for  
20 any player. The invention is performed, in accord with one aspect, by altering the video image slightly using any of a variety of different mapping functions during encoding to warp the video image by a small amount. The mapping function may change from time to time, such as periodically, using small changes of pixel position on the screen, or sharper changes upon significant scene changes. In a preferred embodiment, each time a video is played, the player  
25 will select randomly among a finite number of mapping functions applied during encoding of the video bitstream.

Pixels thus are shifted in position and must be realigned to the original pixel positions in the reproduced video upon decoding so that the image will not appear distorted. A pirate will be able to perform the necessary realignment of pixels only by doing so for each legitimate copy  
30 combined to make an unauthorized master copy of a video. This work on the part of the pirate is made more difficult by the fact that the pirate will not have possession of the original. The position shift furthermore prevents the pirate from being able to remove the watermarks by

discerning the corresponding correlation function by well known video techniques, such as taking the average or multiplexing among the N copies.

In accord with another aspect of the invention, watermark data, other data or software may be downloaded from a service provider by embedding the data or software in the analog channel of the video supplied by the provider to the user. This is in contrast with conventional systems sending data to the user during the non-active portions of a video signal, such as during the blanking interval of an NTSC waveform. The software may comprise programming for changing the functionality of equipment in the hardware platform at the user terminal, e.g., encryption implemented in the encoder of a player. Preferably, local error correction is performed on the received software, where no handshaking with the provider is carried out. The data in practice will be downloaded at a rate sufficiently high such that the image may be disturbed. However, in general, downloading will be relatively brief or performed while the television or monitor is not being used and may be intentionally blanked.

Another aspect of the invention is an alternative to storing a table of CDMA waveform values used for encoding the running mark data that is produced each time a DVD is played as described in the copending application. In accord with the invention, CDMA waveform values are carried, column by column, in the running mark pack within the video bitstream. Preferably, up to two columns of the CDMA waveform values are embedded in a running mark pack. During encoding, the incoming encrypted bitstream contains the original video data and running mark packs. The CDMA table column values are added by to the running mark pack by vectoring to the bottom end of a pack and storing upward. In the preferred embodiment a single column of values may be derived from bits of different columns of the CDMA table, for enhanced security. Flexibility is enhanced because the columns being carried by the running mark pack may be changed during play.

In another aspect of the invention, the data structure implemented in the MPEG bitstream of running mark system is comprised of a header followed by successive data regions. Between the header and first data region, and between successive data regions is an unused portion. A pointer from the header or from any data region to the next data region, jumping over the unused portion, enables the unused portion to be filled by future program expansion such as watermark insertion, encryption, etc.

In accord with yet another aspect, in which the bitstream containing video, audio and watermark data is in MPEG-2 packets, the particular packet to which watermark data is to be

added by message hole replacement is uniquely identified. This is done, either by packet counting that is inherently unreliable in the presence of noise, or by packet numbering that is complicated and adds to overhead, or by signature. In the preferred embodiment, the signature of a packet is derived from the stream identification (stream\_id) and presentation time stamp (PTS) of a packet, defined in the MPEG-2 standard for packetized elemental streams (PES). The stream\_id, describing the type of packet, and PTS describing time interval within a packet for synchronization purposes, together form a signature that is usually capable of identifying the location of a particular bit within the bitstream. If a packet does not contain a PTS, the packet location in a bitstream is identified by offset from a previous packet having a PTS. Absolute location can be used to locate a packet when there is no available signature. To reduce ambiguities, and enhance robustness, more than one signature can be employed, or signature in combination with an absolute or relative address, may be implemented to identify a packet location.

In accord with still another aspect of the invention, to reduce the amount of re-encoding performed at the encoder, to maintain the packet length constant so as to prevent control buffer overflow/underflow, some of the re-encoding is performed at the service provider. This methodology reduces the amount of processing necessary at the player hardware.

### **Brief Description of the Drawings**

Fig. 1 is a high-level block diagram showing the hardware platform of a user terminal in which the invention is implemented.

Fig. 2 shows the terminal interconnected with television and recorder appliances at a user facility.

Fig. 3 shows the user terminal interconnected with a device in which there is no digital link, for describing an aspect of the invention.

Fig. 4 shows a multiple player environment, in which image modification per another aspect of the invention is implemented.

Fig. 5 depicts graphs depicting image mapping and re-alignment implementing an embodiment of image modification in accord with the invention

Figs. 6 and 7 are block diagrams of watermark inserter and extractor systems implementing image modification.



Fig. 8 is a diagram of the data structure of a RMG\_PCK used for carrying CDMA table data, in accord with another aspect of the invention.

Fig. 9 is a diagram showing processing of column data carried by the RMG\_PCK, in the invention.

5 Fig. 10 shows an expandable MPEG-2 compatible bitstream packet, in accordance with a further aspect of the invention.

Fig. 11 shows packet identification using packet signatures per another aspect of the invention.

10 Figs. 12(a)-(d) show exemplary scan patterns, wherein Fig. 12(a) represents the four horizontal rectangular scans (horizontal =1), Fig. 12(b) represents the four vertical rectangular scans (horizontal =0), Fig. 12(c) represents the four zigzag scans for horizontal =1, and Fig.12(d) represents the four zigzag scans for horizontal=0, and wherein the circular dot denotes the first corner of a rectangle.

15 Fig. 13(a)-(d) represent chain coding, wherein Fig. 13(a) represents a sample coding scheme, Fig. 13(b) represents a contour segment, Fig. 13(c) is a chain-coded representation and Fig. 13(d) shows a contour segment code.

Fig. 14 shows different types of time warping functions applied to video.

Fig. 15 represents a partition of an image frame, with each partition warped by a different function.

20 Fig. 16 shows message holes in a video stream.

Fig. 17 shows the use of reference packets and offset information to search for the target packet.

Fig. 18 shows the use of group signatures (patterns) and string matching to search for a particular packet.

25 Fig. 19 shows bits being extracted to be sent from  $B_c[]$ .

### **Best Mode for Practicing the Invention**

Proposed image and video watermarking techniques can be divided into categories baed upon the domain in which they operate: spatial domain, or transform domain. Spatial domain  
30 techniques immerse the watermark into uncompressed video data, e.g., by directly modifying

pixel values. The uncompressed video may be video that has not been compressed or video that has been obtained by decompressing a compressed video. Transform domain techniques compute a transformation (like the FFT, DCT, or wavelet transforms) of part of the video, insert the watermark by modifying the coefficient values, and compute the inverse transform to obtain the watermarked video.

The complexity of spatial domain techniques can be moderate. For example, suppose the watermark is a noise-like pseudo-random sequence that is added to the luminance pixel values comprising a video. A hardware implementation of a pseudo-random generator requires only a few gates and a software implementation is not computationally complex. Spatial domain techniques are not constrained by the MPEG bitstream format. For instance, it is possible to spread the watermark throughout the entire video if every pixel in every frame is modified. Of course, it is convenient to use spatial domain techniques only when the uncompressed video is available (before compression or after decompression). Otherwise, it would be necessary to decode the compressed bitstream, insert the watermark, and reencode the video, which is costly and time-consuming. It is likely that, for the next few years, many consumer electronics devices with digital video capabilities will not give the consumer access to the unencrypted MPEG bitstream. Instead, the video will be accessible as an analog video signal (e.g., composite or s-video). Watermarking techniques that operate in the spatial domain on uncompressed video can protect the video at these outputs and are viable for such devices.

Transform domain watermarking techniques often have high complexity. Usually, a DCT, FFT, or wavelet transform of an entire image and its inverse is computed. The computational burden is substantial. If the watermark needs to be added to an MPEG bitstream, decoding and reencoding also are required. Despite the high complexity, transform domain techniques are the most common approach to watermarking (at least, when computational complexity is not an issue). The relevance of these transforms, especially the DCT and wavelet, to human perception is a major reason for this popularity. Another reason is that these transforms are natural operating domains for spread spectrum techniques. The MPEG bitstream format does not impose any constraints in the transform domain. It is possible, however, for some transform domain techniques to take advantage of the  $8 \times 8$  DCTs in the MPEG bitstream.

The method of Swanson, Zhu, and Tewfik is an interesting example of a transform domain technique. The (uncompressed) video to be watermarked is segmented into scenes. A 3D ( $x$ ,  $y$ , and  $t$ ) wavelet transform of each scene is computed. By computing the wavelet temporally as

well as spatially, it is possible to spread the watermarks across a greater portion of the video. For instance, the watermark embedded in the lowest frequency wavelet coefficient exists throughout all frames in the scene. A model of the human visual system is used to assess how much each wavelet coefficient can be modified without introducing a noticeable degradation of the video. The model takes into account frequency masking and spatial masking effects. The watermark is embedded into the video by modifying the wavelet coefficients to the extent indicated by the model and computing the inverse wavelet transform.

The watermarking process is configured and controlled by a series of messages that are present in an auxiliary bit stream such as a private data stream. Message types that form the core functionality of a watermarking system are defined in this document. To allow for future expansion, it is possible to define new messages and add additional features to existing messages. Where practical, the messages have been designed according to object oriented principles. For example, many messages are a combination of a reference to an object (e.g., some data structure maintained by an OPIMA terminal), an action (method) to be performed on that object, and any other parameters needed to carry out the requested action. The messages, objects, and methods have been designed to be as general as practicable. It should be possible to implement a wide variety of watermarking techniques by combining the various messages in different ways.

Many watermark techniques operate in the frequency domain by modifying the spectral characteristics of a video, but a watermark can be placed in the spatial (pixel) domain of a video. Watermarking in the spatial domain has some interesting advantages. For instance, some digital video display devices have the ability to scale the video after it is decoded, e.g., to convert NTSC to a format suitable for display on a computer monitor. The detrimental effect that this scaling has on the watermark can be avoided if it is possible to insert the watermark into the video in the spatial domain after the video has been scaled. Also, if watermarks are inserted directly into an MPEG-2 video stream in an I or P frame, the watermark can affect the display of several frames, which may make the watermark more easily perceived. Of course, one disadvantage of placing watermarks in the spatial domain is that it is not possible to protect an MPEG-2 video stream without decoding and re-encoding at least part of the video.

The spatial domain watermarking concepts presented in this section concentrate on the watermarking of each picture (frame) comprising the video. A picture might be obtained by

decompressing an unwatermarked MPEG bitstream. The picture is a rectangular array (matrix) of pixel values:

$$v_{i,j}, \quad i = 0, 1, 2, K, I-1, \quad j = 0, 1, 2, K, J-1.$$

Watermarking produces a picture,  $v'_{i,j}$  with some bits hidden in it, e.g., some of the bits comprising the bit string denoted by  $B_e$ . A bit or a group of bits are inserted into a picture by modifying a rectangular region of the picture:

$$v'_{i,j} = \begin{cases} r_l(v_{i,j}, x_{i-i_0, j-j_0}), & \text{if } 0 \leq i-i_0 < M \text{ and } 0 \leq j-j_0 < N, \\ v_{i,j}, & \text{otherwise,} \end{cases}$$

where  $x_{m,n}$ ,  $m = 0, 1, 2, K, M-1$ ,  $n = 0, 1, 2, K, N-1$  is the watermark (a matrix),  $(i_0, j_0)$  is the location (coordinates) in the picture of the upper left corner of the modified rectangular region, and  $r_l$  is some insertion (modulation) method, such as one of those listed in Table 1.  $\alpha_A$ ,  $\alpha_P$ , and  $\alpha_E$  are parameters that control the strength of marks that are inserted by addition, multiplication, and exponentiation, respectively. This insertion process corresponds to watermark modulator 1 in Figure 7. Note that the insertion process may be repeated to insert as many watermarks as desired into a picture.

15

Table 1. Watermark Insertion Methods

<i>Insertion Method</i>	<i>Insertion Function</i>
replace	$r_0(v, x) = x$
add	$r_1(v, x) = v + \alpha_A \cdot x$
product	$r_2(v, x) = v \cdot (1 + \alpha_P \cdot x)$
exponential	$r_3(v, x) = v \cdot \exp(\alpha_E \cdot x)$

Suppose a watermark that represents a single bit is introduced into the picture. This watermark is given by,

$$x_{m,n} = \begin{cases} x_{m,n}^0, & \text{if } b_i = 0, \\ x_{m,n}^1, & \text{if } b_i = 1, \end{cases}$$

where  $b_i$  is the bit (e.g., the  $i$ th bit of the bit string,  $B_e$ ) and  $x_{m,n}^0$  and  $x_{m,n}^1$  are the versions of the watermark associated with a bit value of 0 and 1, respectively.  $x_{m,n}^0$  and  $x_{m,n}^1$  are matrices of

values. Each of these matrices are the same size (have the same dimension) as  $x_{m,n}$ . For clarity, in the remainder of this section, matrices like  $x_{m,n}^0$  and  $x_{m,n}^1$  are referred to as *marks*, whereas the term watermark is reserved for matrices and collections of matrices like  $x_{m,n}$ . Now suppose that a watermark represents 2 bits:

$$x_{m,n} = \begin{cases} x_{m,n}^0, & \text{if } b_{i+1} = 0 \text{ and } b_i = 0, \\ x_{m,n}^1, & \text{if } b_{i+1} = 0 \text{ and } b_i = 1, \\ x_{m,n}^2, & \text{if } b_{i+1} = 1 \text{ and } b_i = 0, \\ x_{m,n}^3, & \text{if } b_{i+1} = 1 \text{ and } b_i = 1, \end{cases}$$

where  $b_i$  and  $b_{i+1}$  are two adjacent bits, e.g., from the bit string,  $B_e$ , and  $x_{m,n}^0$ ,  $x_{m,n}^1$ ,  $x_{m,n}^2$ , and  $x_{m,n}^3$  are four marks associated with the two bits having a combined value of 00, 01, 10, and 11, respectively. To represent three bits with one watermark, eight marks would be needed. Of course, this approach can be extended to an arbitrary number of bits,  $K$ , which would require  $2^K$  marks:  $x_{m,n}^k$ ,  $k = 0, 1, 2, \dots, K-1$ . As described subsequently, sometimes it is more efficient if the picture is not modified when all the bits are equal to 0, i.e., the case of all the bits being 0 is represented by the absence of a mark. This case is equivalent to the first mark being 0 ( $x_{m,n}^0 = 0$ ,  $m = 0, 1, 2, \dots, M-1$ ,  $n = 0, 1, 2, \dots, N-1$ ). The method of encoding multiple bits into a single watermark is analogous to a technique commonly used in digital communications where multiple bits can be represented with one set of modulations. For example, in QPSK, 2 bits are represented by four different phase shifts.

Before delving into the syntax of the various watermarking messages, it is worthwhile to explain some concepts that are used repeatedly in the messages. Most messages begin with a class identification number (**class\_id**) that uniquely identifies the type (class) of object which is the subject of the message. The **class\_id** values can be selected so that they also serve as start codes or resynchronization markers like those used in MPEG-2 sequence, GOP, picture, and slice headers, e.g., in the event of a loss of data due to a communication error. Most messages also contain an object identification number (**obj\_id**) that identifies the particular object which is the subject of the message. Two objects belonging to the same class would never have the same **obj\_id** value, but two objects from different classes might have the same **obj\_id**. To uniquely reference (designate) a particular object requires both the **class\_id** and **obj\_id**. Most messages are requests for the performance of some action, which is designated by a method code (**method**). Two different methods in the same class would never have the same **method**

code, but two methods in different classes could have the same code. A particular method is uniquely identified by the combination of **class\_id** and **method**. Some messages invoke methods to create (construct) or delete (destroy) an object belonging to a particular class (designated by **obj\_id** and **class\_id**). Objects are persistent; once created they continue to exist  
 5 until they are explicitly destroyed or the content stream ends. If a message requests the construction of an object that already exists, the effect is the same as if the existing object has been destroyed and another object subsequently constructed. It is the responsibility of the designer of the messages to ensure that **class\_id**, **obj\_id**, and **method** values are correct.

The syntax defined in this section enables the following general approach to spatial domain  
 10 watermarking:

- Build a collection of marks stored in the terminal. Each mark can be transmitted to the terminal in the body of a message or a message can instruct the terminal to construct the mark using a given algorithm and parameters.
- Insert the marks into the video to represent the bits comprising the watermark.
- 15 • Replace or delete marks from the collection, if needed.

Using this approach, it is possible to implement different watermarking strategies. For instance, if sufficient bandwidth or computing power is available, different marks can be used for each transmitted bit by sending a different set of marks to the terminal for each bit. If bandwidth or computing power is at a premium, a set of marks can be sent to the terminal once  
 20 and used for the entire duration of the content.

For spatial watermarking, a mark object (one of the  $x_{m,n}^k$  matrices) is a matrix of values that can be used to modify a rectangular region of equal size in an uncompressed video frame. At present, the mark can be either a pseudo-random pattern automatically generated by a pseudo-random number generator in the terminal or a given array of values. The syntax for a mark is  
 25 listed in Table 2. There are four methods (actions) for a mark: construct a pseudo-random mark (*constructRandom*), construct a mark from the given matrix element values (*constructMatrix*), delete the mark (*destroy*), and insert the mark into a picture (*insert*). To construct a pseudo-random mark, the insertion method type ( $r_i$ ), the dimensions (size) of the mark ( $M$  and  $N$ ), and the pseudo-random generator must be specified. The insertion method type is included in a  
 30 mark object so that some intermediate values (such as  $\alpha_A \cdot x$ ) can be cached within the terminal, if desired. The pseudo-random generator object is created separately (by another message, described subsequently) and incorporated into a mark object by reference. The generator object

provides a pseudo-random value for each element of the mark matrix. To construct a mark from matrix elements, the insertion method type and the matrix element values are given. An example syntax is listed in Table 3. More efficient and more convenient representations of this data are sought. When a mark object is destroyed, all the storage associated with it is released, i.e., the

5 matrix is deleted. The *insert* method embeds a mark into the picture. This method is provided to allow the insertion of a static watermark, i.e., a watermark that does not depend on any bit values ( $b_i$ ). The size of the mark and the insertion method type are given when the mark is constructed, so the only additional information required is a reference to the picture where the mark should go ( $v_{i,j}$ ) and the location in that picture corresponding to the upper left corner of

10 the mark,  $(i_0, j_0)$ .

Table 2. Spatial Video Mark Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
SpatialVidMark() {		
class_id	TBD	bslbf
method	TBD	bslbf
obj_id	TBD	uimsbf
if (method == constructRandom) {		
VidMarkInsertType()		
x_size	11	uimsbf
y_size	11	uimsbf
PseudoRandomGeneratorRef()		
} else if (method == constructMatrix) {		
VidMarkInsertType()		
SpatialVidMarkPic()		
} else if (method == destroy) {		
} else if (method == insert) {		
PictureRef()		
X	11	uimsbf
Y	11	uimsbf
}		
}		
SpatialVidMarkRef() {		
class_id	TBD	bslbf
obj_id	TBD	bslbf
}		

**class\_id:** A constant bit string (TBD) which identifies the object as belonging to the SpatialVidMark() class.

**method:** A code that indicates the action (method) to be performed.

5 **obj\_id:** A value which uniquely identifies an object in the SpatialVidMark() class.

VidMarkInsertType(): The insertion method type, which specifies how the mark should be inserted into the video (see Table 13).



**x\_size**: The horizontal dimension of the mark ( $N$ ).

**y\_size**: The vertical dimension of the mark ( $M$ ).

**PseudoRandomGeneratorRef()**: The pseudo-random number generator to be used to generate the mark (see Table 12).

- 5 **SpatialVidMarkPic()**: The mark, represented as a small rectangular matrix (image). See Table 3.

**PictureRef()**: Specifies which picture (video frame) the mark should be inserted into.

**x, y**: The x, y coordinates, in the picture, where the top left corner of the mark is inserted ( $i_0, j_0$ ).

10 Table 3. Spatial Video Mark Picture Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
<b>SpatialVidMarkPic()</b> {		
<b>x_size</b>	11	uimsbf
<b>y_size</b>	11	uimsbf
<b>pel_width</b>	TBD	uimsbf
for ( $j = 0; j < y\_size; j++$ ) {		
for ( $i = 0; i < x\_size; i++$ ) {		
<b>pel</b>	pel_width	tcimsbf
}		
}		
}		

**x\_size**: The horizontal dimension of the mark ( $N$ ).

**y\_size**: The vertical dimension of the mark ( $M$ ).

**pel\_width**: The value of this integer equals the number of bits used to represent each element of the matrix.

- 15 **pel**: A signed integer value representing one of the elements of the matrix.

The syntax for controlling the insertion of marks is listed in Table 4. A **SpatialVidBitInserter()** object is a collection (list) of marks,  $x_{m,n}^k$ ,  $k = 0, 1, 2, K, 2^K - 1$ , any one of which is inserted into the video depending on the value of a bit or a group of bits from a bit string source ( $B_e$ ). This object also contains a reference to the picture (frame) into which the

20

marks are inserted ( $v_{i,j}$ ) and the x, y coordinates in that picture where the mark should be placed ( $i_0, j_0$ ). The *construct* method constructs a SpatialVidBitInserter() object from these constituent data structures. The *destroy* method deletes an object. The *insert* method extracts **num\_bits** bits from the bit string source and inserts the corresponding mark into the picture at the coordinates that were specified when the object was constructed.

Table 4. Spatial Video Bit Inserter Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
SpatialVidBitInserter() {		
class_id	TBD	bslbf
method	TBD	bslbf
obj_id	TBD	uimsbf
if (method == construct) {		
BitSourceRef()		
PictureRef()		
X	11	uimsbf
Y	11	uimsbf
no_zero_mark	1	uimsbf
num_bits	TBD	uimsbf
for (i = 0; i < ((1<<num_bits) - no_zero); i++) {		
SpatialVidMarkRef()		
}		
} else if (method == destroy) {		
} else if (method == insert) {		
}		
}		

**class\_id:** A constant bit string (TBD) which identifies the object as belonging to the SpatialVidBitInserter() class.

**method:** A code that indicates the action (method) to be performed.

10 **obj\_id:** A value which uniquely identifies an object in the SpatialVidBitInserter() class.

BitSourceRef(): Specifies a bit string source ( $B_e$ ) that controls which mark gets inserted.

PictureRef(): Specifies which picture (video frame) the mark should be inserted into (see Table 11).

**x, y:** The x, y coordinates, in the picture, where the top left corner of the mark is located  $(i_0, j_0)$ .

- 5 **no\_zero\_mark:** If no\_zero\_mark = 0, there is one mark for each possible value of the bit or group of bits and the number of mark references is  $2^{\text{num\_bits}}$  (or  $2^K$ ). If no\_zero\_mark = 1, no mark is inserted when the bit or bits are equal to 0. In this case, 0 is represented by the original video, i.e., the absence of a mark. This situation is equivalent to the first mark being 0 ( $x_{m,n}^0 = 0, m = 0, 1, 2, K, M-1, n = 0, 1, 2, K, N-1$ ) and, consequently, it is not necessary to
- 10 provide a reference for the first mark so that the number of mark references is  $2^{\text{num\_bits}} - 1$  (or  $2^K - 1$ ).

**num\_bits:** The value of num\_bits equals the number of bits represented by this collection of marks (K). For instance, num\_bits = 1, if 1 bit is represented, num\_bits = 2 for 2 bits, and num\_bits = 3 for 3 bits.

- 15 **SpatialVidMarkRef():** A reference to a mark (see Table 2).

To help illustrate how a sequence of messages might be designed to implement a simple spatial watermarking technique, consider the messages illustrated in Table 5. A normally distributed pseudo-random number generator with a mean of 0 and a standard deviation of 4 is

20 constructed and used to fill the elements of two mark matrices (image) that are 32 pixels wide and 12 pixels high. The mark will be inserted by adding it directly to the picture (video frame) pixel values without any scaling (since the amplitude is 1). A spatial video bit inserter is constructed that will, when requested, insert the second mark at coordinates (382, 186) in the referenced picture if the next bit extracted from the bit string is a 0 and will insert the first mark

25 if it is a 1. Next, this bit is inserted into the picture. Finally, all the objects that were constructed (created) are destroyed.

Table 5. Example Watermarking Session

```
/* Construct a normally distributed pseudo-random number generator object. */
PseudoRandomNumberGenerator() {
    class_id = PseudoRandomNumberGenerator, method = constructNormal, obj_id = 1
    seed = 777,      mean = 0, std_dev = 4
}
```

```
/* Construct the first mark . */
SpatialVidMark() {
    class_id = SpatialVidMark, method = constructRandom, obj_id = 1
    VidMarkInsertType() { insert_type = add, amplitude = 1 }
    x_size = 32, y_size = 12
    PseudoRandomNumberGeneratorRef() { class_id = PseudoRandomNumberGenerator,
obj_id = 1 }
}
/* Construct the second mark. */
SpatialVidMark() {
    class_id = SpatialVidMark, method = constructRandom, obj_id = 2
    VidMarkInsertType() { insert_type = add, amplitude = 1 },
    x_size = 32, y_size = 12
    PseudoRandomNumberGeneratorRef() { class_id = PseudoRandomNumberGenerator,
obj_id = 1 }
}
/* Construct a bit inserter (a list of the 2 marks). */
SpatialVidBitInserter() {
    class_id = SpatialVidBitInserter, method = construct, obj_id = 1
    BitSourceRef() { TBD }
    PictureRef() { TBD }
    x = 382, y = 186
    no_zero = 0, num_bits = 0
    SpatialVidMarkRef() { class_id = SpatialVidMark, obj_id = 1 }
    SpatialVidMarkRef() { class_id = SpatialVidMark, obj_id = 2 }
}
/* Insert the appropriate mark, depending of the bit value. */
SpatialVidBitInserter() {
    class_id = SpatialVidBitInserter, method = insert, obj_id = 1
}
/* Destroy the bit inserter. */
SpatialVidBitInserter() {
    class_id = SpatialVidBitInserter, method = destroy, obj_id = 1
```

```

}
/* Destroy the second mark. */
SpatialVidMark() {
    class_id = SpatialVidMark, method = destroy, obj_id = 2
}
/* Destroy the first mark. */
SpatialVidMark() {
    class_id = SpatialVidMark, method = destroy, obj_id = 1
}
/* Destroy the pseudo-random number generator. */
PseudoRandomNumberGenerator() {
    class_id = PseudoRandomNumberGenerator, method = destroy, obj_id = 1
}

```

Instead of dealing with pixel values, the transform domain watermarking concepts discussed in this section consider a matrix of transform coefficients:

$$v_{i,j}, \quad i = 0, 1, 2, K, I-1, \quad j = 0, 1, 2, K, J-1.$$

- 5       The transform could be the DCT, FFT, a wavelet, or some other transform. The elements of the matrix could be scalar values or complex numbers. The matrix is the transform of a rectangular region of a picture (frame) comprising the video. For example, it might be an 8×8 DCT (a block) or the 720×480 FFT of an entire NTSC frame. Watermarking hides some bits (e.g., from  $B_c$  in Figure 6) in these coefficients by inserting the watermark in some of the
- 10   coefficient values:

$$v'_{s_m, t_m} = r_l(v_{s_m, t_m}, x_m), \quad m = 0, 1, 2, K, M-1,$$

- where  $v'_{s_m, t_m}$  are the modified transform coefficients,  $x_m$ ,  $m = 0, 1, 2, K, M-1$  is the watermark (a vector),  $(s_m, t_m)$ ,  $m = 0, 1, 2, K, M-1$  is a list of locations (row and column coordinates) of the coefficients that are to be modified, and  $r_l$  is some insertion (modulation)
- 15   method (see Table 1). The list of locations,  $(s_m, t_m)$ , allows any arbitrary subset of the transform coefficients to be modified and is easily implemented in software as illustrated in the following C code fragment:

```

void insert (
    int v_prime[I][J], int v[I][J], int x[M], int s[M], int t[M]
)
{
    int rl(int,int);
    int m;
    for (m = 0; m < M; m++) {
        v_prime[s[m]][t[m]] = rl( v[s[m]][t[m]], x[m] );
    }
}

```

The list of locations generalizes the concept of the zigzag scan pattern used to access the DCT coefficient values in MPEG. The remaining transform coefficients (those not in the list) are not modified:

$$v'_{i,j} = v_{i,j}, \quad \text{if } (i,j) \notin \{(s_m, t_m) : m = 0, 1, 2, K, M-1\}.$$

Watermark insertion by this method corresponds to watermark modulator 1 in Figure 6. The insertion process can be repeated to insert as many bits as needed into the transform coefficients.

Consider a watermark that represents a single bit. Similar to the spatial domain case, this watermark is given by,

$$x_m = \begin{cases} x_m^0, & \text{if } b_i = 0, \\ x_m^1, & \text{if } b_i = 1, \end{cases}$$

where  $b_i$  is the bit (e.g., the  $i$ th bit  $B_e$ ) and  $x_m^0$  and  $x_m^1$  are the marks associated with a bit value of 0 and 1, respectively.  $x_m^0$  and  $x_m^1$  are vectors that are the same size as  $x_m$ . As in the spatial domain case, if a watermark represents 2 bits,  $b_i$  and  $b_{i+1}$ , four marks  $x_{m,n}^0$ ,  $x_{m,n}^1$ ,  $x_{m,n}^2$ , and  $x_{m,n}^3$  are used to denote the four possible values of 2 bits: 00, 01, 10, and 11. To represent three bits with one watermark requires eight marks. Extending these examples to an arbitrary number of bits,  $K$ , would require  $2^K$  marks:  $x_m^k$ ,  $k = 0, 1, 2, K, 2^K - 1$ . An alternative is to use the absence of a mark to represent the case where all the bits are 0. This alternative is the same as the first mark being equal to 0 ( $x_m^0 = 0$ ,  $m = 0, 1, 2, K, M-1$ ).

The messages defined in this section are intended to allow the following approach to transform domain watermarking:

- Build a collection of transform domain marks in the terminal. A mark can be sent to the terminal in a message or the terminal can construct the mark using an algorithm and parameters specified by a message.
- Compute the transform of a section of a picture (frame).
- 5   • Insert the mark into the transform coefficients.
- Perform the inverse transform and put the resulting section of a frame back into the original picture.
- Replace or delete marks from the collection as necessary.

Various watermarking strategies can be realized in this manner.

- 10     The transform domain mark syntax is listed in Table 6. This mark is a vector (a 1-dimensional array) of transform coefficient values ( $x_m^k$ ). The values can be either a pseudo-random sequence or they can be provided in the message. The methods (actions) that can be performed on a mark are: construct a pseudo-random mark (*constructRandom*), construct a mark from the given array of coefficients (*constructArray*), delete the mark (*destroy*), and insert
- 15   the mark (*insert*). To construct a pseudo-random mark, the transform type (DCT, FFT, wavelet, etc.), the insertion method type ( $r_l$ ), the number of coefficients ( $M$ ), and the pseudo-random generator are specified. Another message (see Table 12) creates a pseudo-random number generator object and a reference to it provided when constructing a mark. The insertion method type is specified when the mark is constructed so that some of the intermediate values (such as
- 20    $\alpha_A \cdot x$  in Table 1) can be cached within the terminal, if desired. To construct a mark from an array of coefficients, the same data is needed except that an array (list) of transform coefficient values replaces the pseudo-random number generator. The coefficient values can be scalars or complex numbers. Destroying a mark releases the storage associated with it. The mark is inserted into the transform by the *insert* method. This method does not use any bit values ( $b_i$ );
- 25   a static watermark is inserted. The insertion method type and the number of coefficients in the mark are given when the mark is constructed. A reference to the transform coefficients ( $v_{i,j}$ ) that the mark is inserted into and a reference to the list of locations to be modified (a scanning pattern), ( $s_m, t_m$ ), is the only additional information required.

Table 6. Transform Domain Video Mark Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
TransformVidMark() { class_id method obj_id if (method == constructRandom) { transform_type VidMarkInsertType() num_coeffs PseudoRandomGeneratorRef() } else if (method == constructArray) { transform_type VidMarkInsertType() num_coeffs for (i = 0; i < num_coeffs; i++) { TransformCoeff(transform_type) } } else if (method == destroy) { } else if (method == insert) { VidTransformRef() ScanPatternRef() } }	TBD TBD TBD  TBD  TBD  TBD  TBD	bslbf bslbf uimsbf  bslbf  uimsbf
TransformVidMarkRef() { class_id obj_id }	TBD TBD	bslbf uimsbf
TransformCoeff(transform_type) { if (transform_type == dct) { dct_coeff } else if (transform_type == fft) { real_fft_coeff imag_fft_coeff } else if (transform_type == wavelet) { TBD } }	TBD  TBD TBD TBD	tcimsbf  TBD TBD

**class\_id:** A constant bit string (TBD) which identifies the object as belonging to the TransformVidMark() class.

- 5 **method:** A code that indicates the action (method) to be performed.



**obj\_id:** A value which uniquely identifies an object in the TransformVidMark() class.

**transform\_type:** A bit string that indicates the type of transform (e.g., DCT, FFT, or wavelet).

**VidMarkInsertType():** The insertion method type ( $r_i$ ), which specifies how the mark should be inserted into the previously computed transform (see Table 13).

5 **num\_coeffs:** This value equals the number of transform coefficients contained in the array ( $M$ )

**PseudoRandomGeneratorRef():** The pseudo-random number generator to be used to generate the mark (see Table 12).

**TransformCoeff(transform\_type):** A transform coefficient value for the given type of transform ( $x_m^k$ ).

10 **VidTransformRef():** Specifies which previously computed transform the mark should be inserted into.

**ScanPatternRef():** A reference to the scanning pattern or list of locations,  $(s_m, t_m)$ , as defined in Table 8, that determines which of the previously computed transform coefficients is modified by insertion.

15 **dct\_coeff:** A DCT coefficient value.

**real\_fft\_coeff:** The real part of an FFT coefficient value.

**imag\_fft\_coeff:** The imaginary part of an FFT coefficient value.

The syntax for inserting transform domain marks is listed in Table 7. The TransformVidBitInserter() class represents a list of marks, any one of which can be inserted into  
 20 the transform depending on the value of a bit or bits from a bit string source (e.g.,  $B_e$ ). The mark is inserted into the set of coefficients obtained from a previously computed transform ( $v_{i,j}$ ), incorporated by reference, VidTransformRef(). A scanning pattern,  $(s_m, t_m)$ , controls which coefficients are modified during insertion and which coefficients are left undisturbed. This scanning pattern is analogous to the zigzag or alternate scanning patterns for DCT coefficients  
 25 in MPEG-2 except that any pattern can be specified and the pattern need not contain all the coefficients in the previously computed transform. After insertion, an inverse transformation is computed and the resulting spatial (pixel) domain values are inserted into the specified picture (frame) at the given x, y coordinates. All these constituent data structures are given when the TransformVidBitInserter() object is constructed using the *construct* method. The object is  
 30 deleted with the *destroy* method. The *insert* method get num\_bits bits from the bit string source and inserts the appropriate mark.

Table 7. Transform Domain Video Bit Inserter Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
TransformVidBitInserter() {		
class_id	TBD	bslbf
method	TBD	bslbf
obj_id	TBD	uimsbf
if (method == construct) {		
BitSourceRef()		
PictureRef()		
X	11	uimsbf
Y	11	uimsbf
VidTransformRef()		
no_zero	1	bslbf
num_bits	TBD	uimsbf
for (i = 0; i < ((1<<num_bits) - no_zero); i++) {		
ScanPatternRef()		
TransformVidMarkRef()		
}		
} else if (method == destroy) {		
} else if (method == insert) {		
}		
}		

**class\_id:** A constant bit string (TBD) which identifies the object as belonging to the TransformVidBitInserter() class.

**method:** A code that indicates the action (method) to be performed.

5 **obj\_id:** A value which uniquely identifies an object in the SpatialVidBitInserter() class.

BitSourceRef(): Specifies a bit string source to be used to control which mark gets inserted.

PictureRef(): Specifies which picture (video frame) the mark should be inserted into (see Table 11).

**x, y:** The x, y coordinates, in the picture, where the top left corner of the mark is located.

10 **no\_zero\_mark:** If no\_zero\_mark = 0, there is one mark for each possible value of the bit or group of bits and the number of mark references is  $2^{\text{num\_bits}}$  (or  $2^K$ ). If no\_zero\_mark = 1, no

mark is inserted when the bit or bits are equal to 0. In this case, 0 is represented by the absence of a mark. This situation is equivalent to the first mark being 0 ( $x_m^0 = 0$ ,  $m = 0, 1, 2, K, M - 1$ ) and, consequently, it is not necessary to provide a reference for the first mark so that the number of mark references is  $2^{\text{num\_bits}} - 1$  (or  $2^K - 1$ ).

5 **num\_bits**: The value of num\_bits equals the number of bits represented by this collection of marks ( $K$ ). For instance, num\_bits = 1, if 1 bit is represented, num\_bits = 2 for 2 bits, and num\_bits = 3 for 3 bits.

**ScanPatternRef()**: A reference to the scanning pattern or list of locations,  $(s_m, t_m)$ , as defined in Table 8, that determines which of the previously computed transform coefficients is modified by  
10 insertion.

**TransformVidMarkRef()**: A reference to a mark (see Table 6).

To select or specify a subset of the coefficient values comprising a 2-D transform such as the DCT, the FFT, or a wavelet transform, the ScanPattern() class is used. The syntax for the class is listed in Table 8. Four types of scanning patterns can be constructed: (1) zigzag, like  
15 the default DCT scanning pattern, (2) rectangular, like the order in which words are put on a page, (3) a list of locations (row and column coordinates), (4) a chain coded scan that is completely specified by data provided when the scanning pattern is constructed. The zigzag and rectangular scans both cover a rectangular area of the transform coefficients. Consequently, the rectangular region that is covered must be specified by giving the row and column (**corner1\_u**  
20 and **corner1\_v**) of the first scanned coefficient in the matrix of transform coefficients and the row and column (**corner2\_u** and **corner2\_v**) of the last scanned coefficient. Also, for each of these scans, there are two different patterns that can fill the rectangle, depending on whether the first step is a horizontal or vertical one (which is specified by the **horizontal** bit flag). These scanning patterns are illustrated in Figure 12. The dot at the base of the arrows indicates the  
25 location given by **corner1\_u** and **corner1\_v**. The corner diagonally opposite is given by **corner2\_u** and **corner2\_v**. The list of locations scanning pattern is a list of row and column pairs,  $(s_m, t_m)$ ,  $m = 0, 1, 2, K, M - 1$ . The chain coded scan is a continuous contour through the transform coefficients that is represented using a *chain code*. From any point in the matrix, a step to any one of the 8 adjacent points in the matrix can be specified by a value between 0 and  
30 7 as illustrated in Figure 13. The contour is represented by the starting row and column (**begin\_u** and **begin\_v**) of the first scanned coefficient and a list of steps (**step\_dir**) to take from there.

Table 8. Transform Scan Pattern Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
ScanPattern() {		
class_id	TBD	bslbf
method	TBD	bslbf
obj_id	TBD	uimsbf
if (method == constructZigZag    method == constructRectangle) {		
corner1_u	11	uimsbf
corner1_v	11	uimsbf
corner2_u	11	uimsbf
corner2_v	11	uimsbf
horizontal	TBD	bslbf
} else if (method == constructLocations) {		
num_locs	TBD	uimsbf
for (i = 0; i < num_locs; i++) {		
u	11	uimsbf
v	11	uimsbf
}		
} else if (method == constructChain) {		
begin_u	11	uimsbf
begin_v	11	uimsbf
num_steps	TBD	uimsbf
for (i = 0; i < num_steps; i++) {		
step_dir	TBD	bslbf
}		
} else if (method == destroy) {		
}		
}		
ScanPatternRef() {		
class_id	TBD	bslbf
obj_id	TBD	uimsbf
}		

**class\_id:** A constant bit string (TBD) which identifies the object as belonging to the ScanPattern() class.

5 **method:** A code that indicates the action (method) to be performed.

**obj\_id:** A value which uniquely identifies an object in the ScanPattern() class.

**corner1\_u, corner1\_v:** For a zigzag or rectangular scan, the row and column of the first scanned coefficient in the matrix of transform coefficients.

**corner2\_u, corner2\_v:** The row and column of the last scanned coefficient.

5 **horizontal:** A bit flag that specifies if the first step in a zigzag or rectangular scan is horizontal or vertical.

**num\_locs:** The number of locations in the list ( $M$ ).

**u, v:** A row and column coordinate pair ( $s_m, t_m$ ).

**begin\_u, begin\_v:** The starting row and column of the first scanned coefficient of a chain  
10 coded scan.

**step\_dir:** A value between 0 and 7 that specifies the direction to take when moving from one coefficient in the matrix of transform coefficients to any one of the 8 adjacent coefficients in the matrix.

The VidTransform() class represents a transform of a rectangular region of a picture (frame)  
15 of the video. The type of transform to be computed, the picture to be used, and the rectangular region must be specified when constructing a VidTransform() object using the *construct* method.

Table 9. Video Transform Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
VidTransform() {		
class_id	TBD	bslbf
method	TBD	bslbf
obj_id	TBD	uimsbf
if (method == construct) {		
transform_type	TBD	bslbf
PictureRef()		
begin_x	11	uimsbf
begin_y	11	uimsbf
end_x	11	uimsbf
end_y	11	uimsbf
} else if (method == destroy) {		
}		
}		
VidTransformRef() {		
class_id	TBD	bslbf
obj_id	TBD	uimsbf
}		

**class\_id:** A constant bit string (TBD) which identifies the object as belonging to the VidTransform() class.

5 **method:** A code that indicates the action (method) to be performed.

**obj\_id:** A value which uniquely identifies an object in the VidTransform() class.

**transform\_type:** A bit string that indicates the type of transform (e.g., DCT, FFT, or wavelet).

**PictureRef():** A rectangular region of pixels in this picture (video frame) is the data source (input) for the transform.

10 **begin\_x, begin\_y:** The x, y coordinates of the top left corner of the rectangular region.

**end\_x, end\_y:** The x, y coordinates of the bottom right corner of the rectangular region.

To allow the capabilities of the watermarking system to be upgraded and extended, it must be possible to define and use new object types (classes) and new methods for these or existing objects. One part of this process is the registration of the new **class\_id** and **method** values, i.e., a set of messages are needed to inform the terminal that these new values can be used. The way in which registration is carried out is necessarily dependent to some extent upon the trusted methodology used to download data and software, like the TMW. For instance, to associate a new value of **class\_id** and **method** with new code (software) that is downloaded to the terminal, it must be possible to refer to the new code in some way that cannot be fully specified until the secure download functions are well-defined. As an alternate approach, the registration of new **class\_id** and **method** values might be included as part of the secure download functions.

Table 10. Registration Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
Registration() {		
class_id	TBD	bslbf
method	TBD	bslbf
if (method == registerClass) {		
new_class_id	TBD	bslbf
} else if (method == registerMethod) {		
existing_class_id	TBD	bslbf
}		
num_methods	TBD	uimbsf
for (i = 0; i < num_methods; i++) {		
method_code	TBD	bslbf
MethodRef()		
}		
}		

**class\_id:** A constant bit string (TBD) which identifies the object as belonging to the Registration() class. There is only one such object, so no **obj\_id** value is needed.

**method:** A code that indicates the action (method) to be performed.

15 **new\_class\_id:** The **class\_id** value for the new class that is being registered.

**existing\_class\_id:** The **class\_id** value of an existing class for which a new method is being registered.

**num\_methods:** The number of new methods being registered.

**method\_code:** The **method** value for each new method that is being registered.

**MethodRef():** A reference to a method that has previously been downloaded to the terminal.

The syntax for messages that manipulate common types of objects is described in this section. The types of objects are: a picture (frame) reference, a pseudo-random number generator, the type of video mark insertion method, a DCT of a section of video, and the scan pattern for scanning through transform coefficients, e.g., DCT coefficients.

In some instances, it is necessary to refer to a particular picture (frame) in a video stream. The syntax in Table 11 specifies a picture reference. Please refer to ISO/IEC 13818-1 for more information on stream IDs and presentation time stamps.

Table 11. Picture Reference Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
PictureRef() {		
video_stream_id	8	uimsbf
pts	33	uimsbf
picture_offset	TBD	uimsbf
}		

**video\_stream\_id:** The video stream ID value, which identifies the referenced video stream.

**pts:** A presentation time stamp (PTS) within the specified video stream. The PTS specifies a particular presentation unit within the video stream.

**picture\_offset:** The number of pictures (frames) beyond the first picture in the presentation unit specified by the PTS value.

A pseudo-random number generator potentially can be used in several places in a watermarking technique. A pseudo-random number generator can be set-up and controlled using the syntax in Table 12. The algorithm used to create the pseudo-random numbers needs to be universally agreed upon since, in many watermarking techniques, the same pseudo-random sequence must be generated in both the watermark inserter and extractor. For this reason, it is also important that, if the construction (creation) of multiple pseudo-random number generator objects is requested, each object should have separate internal state variables. Numbers should be generated only when requested by a message so that the internal state can be recreated if needed.

A pseudo-random number generator is constructed (created) by specifying the seed value, the



distribution, and the parameters of the distribution. Three different distributions are supported: uniform, normal (Gaussian), and discrete. A uniform distribution is specified by the upper and lower bounds of the pseudo-random numbers to be generated. A normal distribution is specified by the mean and standard deviation. A discrete distribution is specified a list of the discrete values the generator can return and the probability of occurrence associated with that value. One example of a discrete distribution is a binary random variable with an equal probability of occurrence for 0 and 1, which is listed in the following table:

Discrete Value	Probability
0	0.50
1	0.50

Table 12. Pseudo-Random Number Generator Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
PseudoRandomGenerator() {	TBD	bslbf
class_id	TBD	bslbf
method	TBD	uimsbf
obj_id	TBD	
if (method == constructUniform) {		
seed	TBD	uimsbf
lower_bound	TBD	tcimsbf
upper_bound	TBD	tcimsbf
} else if (method == constructNormal) {		
seed	TBD	uimsbf
mean	TBD	tcimsbf
std_dev	TBD	tcimsbf
} else if (method == constructDiscrete) {		
num_values	TBD	uimsbf
for (i = 0; i < num_values; i++) {		
discrete	TBD	tcimsbf
prob	16	uimsbf
}		
} else if (method == destroy) {		
} else if (method == setSeed) {		
seed	TBD	uimsbf
}		
}		
PseudoRandomGeneratorRef() {		
class_id	TBD	bslbf
obj_id	TBD	uimsbf
}		

**seed:** The pseudo-random number generator seed. If the specified seed value is TBD, the terminal should compute and use a seed value such that the seed is different each time this option is invoked (e.g., by computing it from the system clock).

**lower\_bound:** The lower bound of the range of values that may be returned by the uniformly distributed pseudo-random number generator.

**upper\_bound:** The upper bound of the range of values that may be returned by the generator.

**mean:** The mean of the normally distributed pseudo-random number generator.

5 **std\_dev:** A value representing the standard deviation of the generator.

**num\_values:** The number of discrete values that may be returned by the pseudo-random number generator

**discrete:** One of the discrete values that may be returned by the generator.

**prob:** The probability of the generator returning the corresponding discrete value, expressed as the numerator of a fraction with a denominator of  $2^{16} = 65536$ . For example, if  $\text{prob} = 16384$ , the probability is  $16384/65536 = 0.25$ . The sum of all the values of prob must equal 65536 (a probability of 1).

15 In several instances, the way a mark should be inserted into the video (or the transform coefficients of a video) must be specified. The syntax in Table 13 is used for such a specification.

Table 13. Video Mark Insertion Type Syntax

<i>Syntax</i>	<i>No. of Bits</i>	<i>Mnemonic</i>
VidMarkInsertType() {		
insert_type	2	bslbf
if (insert_type == replace) {		
} else if (insert_type == add) {		
amplitude	TBD	uimsbf
} else if (insert_type == product) {		
proportion	TBD	uimsbf
} else if (insert_type == exponential) {		
exponent	TBD	TBD
}		
}		

**insert\_type:** A bit string which indicates the mark insertion method (see Table 14).

**amplitude:** A value which corresponds to  $\alpha_A$  that controls the strength of a mark which is added to the video.

**proportion:** A value which corresponds to  $\alpha_P$  that controls the strength of a mark which is multiplied with the video.

- 5 **exponent:** A value which corresponds to  $\alpha_E$  that controls the strength of a mark which is exponentially weighted and multiplied with the video.

Table 14. Video Mark Insertion Methods

<i>insert_type</i>	<i>Bit String</i>	<i>Insertion Method</i>
replace	TBD	$v'_i = x_i$
add	TBD	$v'_i = v_i + \alpha_A \cdot x_i$
product	TBD	$v'_i = v_i \cdot (1 + \alpha_P \cdot x_i)$
exponential	TBD	$v'_i = v_i \cdot \exp(\alpha_E \cdot x_i)$

$v'_i$ : The marked video signal.

$x_i$ : The mark.

- 10  $v_i$ : The original (unmarked) video signal.

$\alpha_A$ ,  $\alpha_P$ ,  $\alpha_E$ : Parameters that control the strength of marks that are inserted by addition, multiplication, and exponentiation, respectively.

It should be noted that  $v'_i$ ,  $v_i$ , and  $x_i$  can denote values in either the spatial or frequency (transform) domains.

## 15 Implementation

Referring now to Fig. 1, a user terminal 100 in a multimedia system, that may be incorporated in, or provided with, a set top box in, for example, an OPIMA compliant terminal, is configured to receive scrambled and possibly encrypted multimedia content from a service or content provider. The multimedia content may comprise audio, video, still picture, software,  
 20 etc., received by way of any suitable link, such as optical fiber, hard wire, RF, etc. The received content is applied to a descrambler 102 that produces descrambled, but still compressed, content in a form that conforms, for example, to MPEG standard. The compressed content, when reproduced, is decoded to produce an analog output that is applied to a television or a monitor, in the case of video content, or to another reproduction device. Watermark data are inserted into  
 25 the data stream and becomes part of the output of the terminal, such that any reproduction of the

output signal developed by the terminal will bear the watermark. The watermark is a digital signal that identifies when and where playback has occurred. For example, the watermark may be in the form of "running marks" of the type described in copending application Serial No. 09/092,898, filed on June 8, 1998 and incorporated herein by reference, that identify the source-of-copying (that is, the DVD, DVD player and time of play). This "source-of-copying" information can be used to trace to the copyist, to control copying, or both, as described in the copending application.

With this background in mind, with reference again to Fig. 1, the compressed content, descrambled by unit 102, can have watermark data inserted either before or after decoding, or can be performed both before and after decoding. Thus, the compressed multimedia content is applied to tracing watermark inserter 104a to provide a digital output that is a bitstream containing both compressed digital content and watermark data, and then to decoder 108a (such as an MPEG-2 decoder) to produce a corresponding first analog output. Alternatively, or additionally, as shown, the compressed digital content can be routed first to decoder 108b and then to tracing watermark inserter 104b to produce a second analog output signal.

The digital output from watermark inserter 104a may be applied to a recorder 112 for recording the content on a recording medium, such as a DVD. The recorder enables recording to be performed only if the bitstream is found by copy protection watermark detector 114 to contain a watermark that permits copying. The watermark may include data that permits copying, prohibits copying or permits limited or conditional copying. Detection of the watermark can be performed by any suitable digital filtering process.

Fig. 2 shows the terminal 100 as it may be connected to a television and analog/digital recording equipment in this invention. Encrypted and compressed multimedia content produced by a content provider, obtained via cable, satellite, etc., is applied to the terminal at line 116. A reverse link 118 enables the terminal to communicate back to the provider, via telephone link or other transmission medium, to transfer billing information, polling, etc., in a known manner. The output of the terminal 100 produces analog and digital signals, separately, as described previously. Analog link 120, corresponding to analog output 1 or analog output 2 in Fig. 1, is applied to TV 122, VCR 124 and digital recorder 126. The digital output 128 of the terminal is applied only to the digital recorder 126. The VCR 124 and digital recorder 126 are supplied to television 122 in a conventional manner.

As explained in the copending application, the watermark, added to the data stream each time playback of content received from a provider or reproduced from a prerecorded medium is played, comprises virtually invisible marks embedded into the compressed digital data stream. These marks may identify the player unit, content source and time of play, to help enable trace to the copyist. The best mode of the invention is described within the context of a video stream produced in an MPEG-2 domain, although it is to be understood that the invention is not limited thereto. For example, the source-of-copying message, embedded in the watermark, can be combined into an audio signal or into software using similar principles. The watermarks are not visible to a viewer, but can be detected and decoded by hardware maintained by an authorized institution. The institution, in possession of a DVD, for example, containing protected material, will play the material using equipment that detects and decodes the watermark. The information embedded in the watermark, for example, the serial number of the player used to make the copy, the serial number of the master from which the copy was made and the time the copy was made, may help the institution trace to the copyist. Alternatively, or in addition, the watermark may contain data that will prevent an unauthorized user to reproduce the content from the master, or limit the number of copies that can be made, as explained previously.

Just as there are many different approaches to digital watermarking, there can be as many, of not more, methods for pirates to attack the watermark system by applying different signal processing techniques. A watermark system must be robust so that the embedded signal is difficult to detect, remove or modify, except by the owner of the protected digital content.

As described in the copending application, a pirate copyist may attempt to attack the running mark system for producing digital watermarks by combining video outputs from multiple playback units. Referring to Fig. 4, a copyist may combine the outputs of N players playing a DVD, or other protected medium, to produce a reproduction from which many copies will be made for illicit distribution. The pirate copy is then made by averaging or simply time-multiplexing among the copies.

This form of attack by a pirate is countered, in accord with the present invention, by adding a further level of signal processing that will alter the image, produced by the playback unit in an imperceptible way. Each playback unit imposes a different alteration, known only to the content owner, so that without correction the image produced by combining copies from multiple playback units will be degraded and unwatchable. Referring to Fig. 5, the image reproduced by each playback unit undergoes a spatial transformation that is dictated by a

mapping function  $F(\theta)$ . Altering of the image may be performed by any conventional image mapping functionality. Each playback unit may have a prescribed mapping function assigned to it, or may select among any number of pre-stored mapping functions, based on a key that could be read from the video stream, read from the DVD or developed in some other manner.

5       The mapping function could, for example, warp the image, shown in Fig. 5, by compressing the spacing between pixels in the vertical direction and expanding the positions in the horizontal direction. The amount of warping is subtle, so that playing a copy made by a single playback unit is not noticed by a viewer. However, when the outputs of many playback units are combined, each with a slightly different mapping function, the composite image will be  
10   distorted (fuzzy) and not of commercial quality. A pirate copy with reasonable picture quality cannot be generated without first re-registering the copies to compensate for the deliberate alteration applied by the content owner. Although the pirate may be able to re-register the pixels, this is time consuming and impractical when an illicit copy made by multiple playback units is involved. In fact, the time required for a pirate to realign copies made by multiple playback  
15   units, each imposing a different mapping function, can be expected to require up to several months or more of labor. This will considerably delay the time when the pirate can distribute usable copies. For the content owner, on the other hand, not re-registration needs to be performed in order to retrieve the original content and watermarks, since the mapping function and its parameters are known and chosen from a pre-defined library.

20       The mapping function may be changed from time to time, such as periodically, to make it more difficult realign pixels if the pirate learns the mapping function. To avoid visible changes in the image reproduced by a single playback unit, the mapping functions preferably are selected such that successive functions alter the image only slightly. (A larger single change in image alignment may be visible, whereas a succession, over time, of several smaller changes may not.)  
25   As another possibility, the mapping function may change at the time of a scene change. In this example, a larger alteration of the image, by mapping, may be tolerated by the viewer.

      Thus, pixels may be shifted in position, by different amounts among different players, and by a different amount each time a medium is played successively by a single player. The pixels must be realigned to the original pixel positions in the reproduced video upon decoding, by the  
30   pirate, so that the image will not appear distorted. A pirate will be able to perform the necessary realignment of pixels only by doing so for each and every copy that is combined to make an

unauthorized master copy of a video. This work on the part of the pirate is made more difficult by the fact that the pirate will not have possession of the original.

The particular mapping function used for altering the image can be selected among many possibilities. Preferably, the function will provide image alteration that is invisible to the viewer,  
 5 easy to apply, quickly generated and robust (not easily reversed by the pirate). The following mapping functions are examples.

A geometric transformation  $f$  on image defines the mapping between two image coordinates,  $(x, y)$  and  $(x', y')$ . To warp one image from another, it is usually more convenient to define the *backward warping* so that each grid point  $(x, y)$  in the target (or warped) frame is  
 10 mapped from a possibly non-grid point  $(x', y')$  in the original frame. Here we define the geometric transformation in terms of backward warping so that  $(x, y)$  is defined on grid points (i.e.,  $x, y \in \mathbb{Z}$ ) while  $(x', y')$  can fall on sub-pixel locations (c.f. Figure 5). The warping can be written as  $(x', y') = f(\Theta, x, y)$  or:

$$\begin{aligned} x' &= f_x(\Theta, x, y) \\ y' &= f_y(\Theta, x, y) \end{aligned}$$

15 Here  $\Theta$  is the parameter set of the transformation. Backward warping is preferred over forward warping because it ensures that every grid point in the target frame has a matching point from the original so that it leaves “no holes” in the target frame. Applying an image interpolation function, the pixel values in the warped frame can then be computed. Popular interpolation schemes are: nearest neighbor, linear interpolation, and bilinear interpolation. A geometric  
 20 transformation is *separable* if  $x' = f_x(x)$  and  $y' = f_y(y)$ ; it is *linear* if both  $f_x$  and  $f_y$  are a linear function of  $x$  and  $y$ .

We intend to apply the geometric transformation to not just one image, but a sequence of images (i.e. a video). One way to achieve this is that instead of applying a 2D spatial geometric transformation, we apply a 3D geometric transformation (spatial and temporal). In this case, the  
 25 warping function warps a 3D volume in the  $(x, y, t)$  space.

$$\begin{aligned} x' &= f_x(\Theta, x, y, t) \\ y' &= f_y(\Theta, x, y, t) \\ t' &= f_t(\Theta, x, y, t) \end{aligned}$$



A simple example of  $f_t$  is frame-dropping or frame-repeating. In general, although the idea of 3D warping is very appealing and more general, for practical reasons, it is more difficult to apply since a large frame buffer is required to store the whole volume of the video and the computation cost is usually high. Another approach that we shall focus on is to apply a  
 5 sequence of 2D geometric transformations to the sequence of image frames, while allowing the parameter set of the warping function to be a function of time.

$$\begin{aligned}x'(t) &= f_x(\Theta(t), x(t), y(t)) \\ y'(t) &= f_y(\Theta(t), x(t), y(t))\end{aligned}$$

In this representation, the warping function remains a 2D geometric transformation at fixed time instant, while at different time both the function form and the parameters can be changed. In the  
 10 following sections, we will first introduce a collection of 2D geometric transformations. Then we will discuss different function forms for achieving temporal warping, i.e.,  $\Theta(t)$ .

Many different representations are available for describing such a transformation for image warping. Table 15 summarizes a collection of geometric transformations that can be used for anti-tamper warping. The size of the parameter set and parameters are listed for comparison.  
 15 Here we also provide some mathematical details of some of these functions.

Table 15. A collection of geometric transformations for anti-tamper warping.

Category	Method	# Parameters	Parameter set $\Theta$
Linear	Translation	2	$t_x, t_y$
	Rotation	3	$\theta, x_0, y_0$
	Scaling	4	$s_x, s_y, x_0, y_0$
	Affine	6	$a_{x'x}, a_{x'y}, a_{y'x}, a_{y'y}, a_{x_0}, a_{y_0}$
Quadratic	Bilinear	8	$a_{x'x^2}, a_{x'xy}, a_{x'y^2}, a_{y'x^2}, a_{y'xy}, a_{y'y^2}, a_{x_0}, a_{y_0}$
	Pseudo-perspective	8	$a_{x'x}, a_{x'y}, a_{y'x}, a_{y'y}, a_{x_0}, a_{y_0}, a_\alpha, a_\beta$
	Biquadratic	12	$a_{x'x^2}, a_{x'xy}, a_{x'y^2}, a_{y'x^2}, a_{y'xy}, a_{y'y^2}, a_{x_0}, a_{y_0}, a_{x_0^2}, a_{x_0y_0}, a_{y_0^2}, a_{x_0^3}, a_{x_0^2y_0}, a_{x_0y_0^2}, a_{y_0^3}$
Higher-order Polynomial	$P(n)$	$2(n+1)$	$2(n+1)$ interpolation points
Rational	$R(n,m)$	$2(n+m+2)$	$2(n+m+2)$ interpolation points
	Projective	8	$a_{x'x}, a_{x'y}, a_{y'x}, a_{y'y}, a_{x_0}, a_{y_0}, a_\alpha, a_\beta$
Spline	Cubic Spline	4 or more/segment	4 control points + other parameters
Motion Transform	Fourier	$2 \cdot  U  \cdot  V $	$M_x(u, v), M_y(u, v) \quad u \in U, v \in V$
	Wavelet	$2 \cdot \sum_l  U_l  \cdot  V_l $	$M_{x,l}(u_l, v_l), M_{y,l}(u_l, v_l) \quad u_l \in U_l, v_l \in V_l$
LUT	1-D	$M + N$	$x \rightarrow x', y \rightarrow y' \quad x = 1 \dots M; y = 1 \dots N$
	2-D	$2MN$	$(x, y) \rightarrow x', (x, y) \rightarrow y' \quad x = 1 \dots M; y = 1 \dots N$

The simplest linear transformation is 2D translation. It simply shifts the entire image by a vector  $(t_x, t_y)$ . Mathematically, it is as simple as:

$$x' = x + t_x$$

$$y' = y + t_y$$

5

Another simple linear transformation is 2D rotation, which has three parameters: the

$$x' = (x - x_0) \cos(\theta) - (y - y_0) \sin(\theta) + x_0$$

$$y' = (x - x_0) \sin(\theta) + (y - y_0) \cos(\theta) + y_0$$

rotation center  $(x_0, y_0)$  and the rotation angle  $\theta$ .

It is also easy to scale the image (zoom in/out). The 2D scaling takes four parameters: the scaling center  $(x_0, y_0)$ , the scaling factor along two image axis  $s_x$  and  $s_y$  respectively.

$$\begin{aligned}x' &= s_x(x - x_0) + x_0 \\y' &= s_y(y - y_0) + y_0\end{aligned}$$

- 5 The most general 2D linear geometric transformation is the affine transformation. It has six parameters and can describe a combination of translation, rotation, scaling, and sheer of the image. Mathematically, it is written as:

$$\begin{aligned}x' &= a_{x'x}x + a_{x'y}y + a_{x'} \\y' &= a_{y'x}x + a_{y'y}y + a_{y'}\end{aligned}$$

- 10 The Quadratic Curves and Surfaces category uses 2<sup>nd</sup> order polynomials to represent the coordinate transformation. The most general formula is the biquadratic transformation with twelve parameters:

$$\begin{aligned}x' &= a_{x'x^2}x^2 + a_{x'xy}xy + a_{x'y^2}y^2 + a_{x'x}x + a_{x'y}y + a_{x'} \\y' &= a_{y'x^2}x^2 + a_{y'xy}xy + a_{y'y^2}y^2 + a_{y'x}x + a_{y'y}y + a_{y'}\end{aligned}$$

- Several commonly used 2<sup>nd</sup>-order transformations can be regarded as degenerated case of the biquadratic transformation. When the  $x^2$  and  $y^2$  terms do not exist (i.e.  $a_{x'x^2} = a_{y'x^2} = a_{x'y^2} = a_{y'y^2} = 0$ ), it is called bilinear transformation, which has eight parameters. When  $a_{y'x^2} = a_{x'y^2} = 0$  and  $a_{x'x^2} = a_{y'xy} = a_\alpha, a_{y'y^2} = a_{x'xy} = a_\beta$ , the transformation is called pseudo-perspective.

- 20 A higher order (greater than three) polynomial or rational functions can be used to generate a more complicated and yet smooth warping function. For simplicity and without loss of generality, we focus on the separable case:  $x' = P_x^{(n)}(x)$  and  $y' = P_y^{(n)}(y)$ , both  $P_x^{(n)}$  and  $P_y^{(n)}$  are an n-th order polynomial. Since an n-th order polynomial contains  $n + 1$  coefficients, it can be uniquely defined by giving  $n + 1$  interpolation points (assuming no three points are colinear). In

the non-separable case, a polynomial surface can be defined. A rational function  $R^{(n,m)}$  is a quotient of two polynomials:

$$R^{(n,m)}(x) = \frac{P^{(n)}(x)}{Q^{(m)}(x)}$$

- 5        where both  $P^{(n)}$  and  $Q^{(m)}$  are polynomials. Projective transformation is a rational function (non-separable) commonly used in image processing to approximate the image change under rigid-body motion and perspective projection. It has the following form:

$$x' = \frac{a_{x'x}x + a_{x'y}y + a_{x'}}{a_{\alpha}x + a_{\beta}y + 1}$$

$$y' = \frac{a_{y'x}x + a_{y'y}y + a_{y'}}{a_{\alpha}x + a_{\beta}y + 1}$$

- Note that there are common parameters in the denominators. Other transformations derived  
 10    from 3D rigid-body motion with a 3D to 2D image projection function (e.g., perspective, para-  
 perspective, orthographic, etc.) may also be considered as the warping function to create the  
 effect of changing the camera viewing angle. However, they usually require the knowledge on  
 the depth of different objects or points in the frame.

- Cubic splines have been widely used in computer graphics applications to generate realistic  
 15    scenes. A cubic spline can be defined by a group of points, called control points. Since each  
 curve segment is a cubic polynomial with four coefficients, at least four constraints are needed,  
 allowing us to formulate four equations and solve the four unknowns. The constraints usually  
 comes from the end points, their tangents, and assumptions on the geometric continuity at the  
 segment boundary. Different cubic splines use different constraints, and their capability to  
 20    interpolate control points vary. For instance, a natural cubic spline interpolates all its control  
 points while uniform B-spline does not interpolate any of its control points. For some splines,  
 extra unknowns (parameters) are used to control the geometric continuity at the segment  
 boundary. To use cubic spline as a warping function, we can apply different splines to x and y  
 axis such as  $x' = f_x(x)$  and  $y' = f_y(y)$ , both  $f_x$  and  $f_y$  are a spline curve. In this case, the

geometric transformation is separable. In the non-separable case, a bicubic spline surface can be defined by given a set of control points in the 2D space. The number of parameters therefore increases significantly. One advantage of using spline function for image warping is that it is easy to control the warping of image boundary so that the boundary can be fixed. This makes the warping much more difficult to detect. Commonly used cubic splines include natural cubic spline(4), Hermite curve (4), Bézier curve (4), Uniform B-spline (4), Nonuniform B-spline (6),  $\beta$ -spline (5), Catmull-Rom curve (4), Kochanek-Bartels curve (7), and so on. (The number in the parentheses shows the number of parameters per curve segment.) For more details on these splines, including their constraints and parameters, please refer to [12].

Applying a geometric transformation to the image can be considered equivalent as applying a motion vector to all the image pixels. This is different from the translation case since the motion vector is a function of the pixel location.

$$\begin{aligned}x' &= x + m_x(x, y) \\ y' &= y + m_y(x, y)\end{aligned}$$

If each  $m_x$  and  $m_y$  is independently specified, it would take too many parameters to describe the motion field. Motion transform uses a small number of parameters to represent the motion vectors  $m_x$  and  $m_y$  in a transform domain (e.g., frequency domain) instead of the image domain. The transform is defined based on a set of basis functions.

$$\begin{aligned}m_x(x, y) &= \sum_u \sum_v M_x(u, v) B(x, y, u, v) \\ m_y(x, y) &= \sum_u \sum_v M_y(u, v) B(x, y, u, v)\end{aligned}$$

and

$$\begin{aligned}M_x(u, v) &= \Psi\{m_x(x, y)\} \\ M_y(u, v) &= \Psi\{m_y(x, y)\}\end{aligned}$$

Here  $B$  denotes the basis function;  $M_x$  and  $M_y$  represent the transformed motion vectors. The transform function  $\Psi\{\cdot\}$  can be DFT (Discrete Fourier Transform), Haar transform, KL

transform, wavelet transform, or others. The indices  $u$  and  $v$  indicate the basis functions included. Suppose  $u$  and  $v$  are chosen from the sets  $U$  and  $V$  (i.e.,  $u \in U$  and  $v \in V$ ). The complexity (or number of parameters) can be represented by  $|U| \cdot |V|$  where  $|\cdot|$  is the number of elements (or cardinality) of the set. The elements in  $U$  and  $V$  can be customized to include some basis  
 5 functions whose span is our interested motion subspace. Next we address two types of basis functions: the Fourier family and wavelet family.

Fourier transform and its relatives have been used for many applications, including image coding. Similar to the way they are used in image coding, their basis functions can also be applied to describe the motion field. We can use DFT (Discrete Fourier Transform), DCT  
 10 (Discrete Cosine Transform), or DST (Discrete Sine Transform) as the motion transform. The basis functions will have the following forms.

$$\text{DFT:} \quad B(x, y, u, v) = \exp(j \cdot 2\pi(\frac{u \cdot x}{M} + \frac{v \cdot y}{N}))$$

$$\text{DCT:} \quad B(x, y, u, v) = \cos(\pi \cdot u \cdot \frac{x + 0.5}{M}) \cos(\pi \cdot v \cdot \frac{y + 0.5}{N})$$

15

$$\text{DST:} \quad B(x, y, u, v) = \sin(\pi \cdot u \cdot \frac{x}{M}) \sin(\pi \cdot v \cdot \frac{y}{N})$$

where  $M$  and  $N$  are the horizontal and vertical size of the frame, respectively.

20 Wavelet functions can be used to describe the warping in a similar way as the Fourier family (or sinusoidal functions). The main difference is that wavelet transform is usually hierarchically applied thereby bearing the multi-resolution concept. Denote the scaling and wavelet function as  $\phi$  and  $\varphi$  for generating the multi-resolution analysis (MRA) in the wavelet representation, the motion transform can be written as:

25

$$m_x(x, y) = \sum_l \sum_{u_l} \sum_{v_l} M_{x,l}(u_l, v_l) B_l(x, y, u_l, v_l)$$

$$m_y(x, y) = \sum_l \sum_{u_l} \sum_{v_l} M_{y,l}(u_l, v_l) B_l(x, y, u_l, v_l)$$

where  $l$  is the index for the resolution level,  $l = -1, 0, \dots, L-1$ . Note that the basis functions included at each level may vary therefore  $u$  and  $v$  become a function of  $l$ .

- 5 In orthogonal wavelet family, the basis functions can be written as a tensor product of the scaling function  $\phi$  and wavelet function  $\varphi$ . At the coarsest level, (i.e.,  $l = -1$ )

$$B_{-1}(x, y, u_{-1}, v_{-1}) = \phi(x - u_{-1})\phi(y - v_{-1})$$

At finer levels (i.e.  $l \geq 0$ ), the basis functions have three forms: horizontal (H), vertical (V), and diagonal (D) depending on the construct from the scaling and wavelet functions.

$$B_l^H(x, y, u_l, v_l) = \phi(2^l x - u_l)\varphi(2^l y - v_l)$$

$$B_l^V(x, y, u_l, v_l) = \varphi(2^l x - u_l)\phi(2^l y - v_l)$$

$$B_l^D(x, y, u_l, v_l) = \varphi(2^l x - u_l)\varphi(2^l y - v_l)$$

10

$$\phi(x) = \frac{1}{6} \sum_{j=0}^4 \binom{4}{j} (-1)^j (x - j)_+^3$$

One example of wavelets is the Cai-Wang wavelet [13,14], in which

where for any real number  $n$

15

And

$$x_+^n = \begin{cases} x^n & \text{if } x \geq 0 \\ 0 & \text{otherwise} \end{cases}$$

$$\phi(x) = -\frac{3}{7}\phi(2x) + \frac{12}{7}\phi(2x-1) - \frac{3}{7}\phi(2x-2)$$

Wavelets and their applications have been very popular recently. Other popular wavelet functions are Haar, Daubechies family, Meyer, Lemarie, and a lot more. For more details, please refer to [15].

5 Look-up table (LUT) is a direct way to describe the coordinate mapping by simply storing the mapping of every image pixel (grid point) in a table so that a simple table look-up gives the mapped location. Since the movement of each pixel has two degree of freedom, in the non-separable case, a table of size  $2MN$  is needed to specify the mapping for an  $M$  by  $N$  image. In the separable case, two arrays (of size  $M$  and  $N$  each) are sufficient. A LUT can also store only  
10 the mapping of a subset of image points to define a mesh structure and be used with different warping functions for each mesh element. They will be further discussed in a later section.

To apply the warping to a video, the warping function can change through time slowly to provide a better protection against pirates' attack. The change must be slow enough so that it does not produce unpleasant visual artifacts. As we have seen that the parameter set itself can  
15 be a function of time,  $\Theta(t)$ , or

$$\Theta(t) = f_t(\Theta_0, t)$$

where  $\Theta_0$  is the initial parameter set.

Similar to the way that the spatial warping is applied, the time-warping function  $f_t$  can be  
20 either linear, quadratic, cubic, or sinusoidal. Most functions shown in Table 15 can be used for time warping as well. Therefore  $f_t$  can be: (c.f. Figure 15)

Piecewise constant: In this case, the parameter set remains constant within a time interval.

Piecewise linear: A saw-tooth-like waveform can be used as the time warping function. Each line segment can be defined by its end points and slope.

25 Quadratic or cubic curve: Same quadratic or cubic curves can be used in the time domain to specify the parameter change through time.



Sinusoidal: Use of sinusoidal function to describe parameter change though time is relatively simple and it does not require a large number of extra parameters. For example, we can specify the  $i$ -th parameter  $\Theta_i$  to have the following form:

$$\Theta_i(t) = \Theta_i(t_0) + A \cdot \sin(w(t - t_0))$$

- 5        where  $\Theta_i(t_0)$  is its value at time  $t_0$ ,  $A$  and  $w$  are the amplitude and angular velocity of the sinusoidal function respectively.

For a long sequence, the form of the time-warping function can be changed at selected time instants, preferably at scene change along the video sequence or black frames, which provides a natural way to insert discontinuity into the time-warping function without causing visual artifacts.

For a more complicated implementation, the warping on a single image can be a result from applying multiple transformations. There are two major ways to apply multiple transformations to an image. One is to apply different warping functions sequentially to the whole or partial image. Suppose a sequence of  $N$  warping functions is applied. Then we have:

$$(x', y') = f_1(f_2(\cdots f_N(x, y))) \quad \forall x, y$$

15

The other approach is to first partition the image and apply different warping functions to

$$\forall (x, y) \in \Omega_i$$

each partition. Therefore,

$$(x', y') = f(x, y)$$

- 20        where  $\Omega_i$  is the  $i$ -th partition of the image (c.f. Figure 16). In this case, how to partition the image is critical to the overall distortion and one should be careful not to cause undesired visual effect by ill choosing the partition, function form, and parameter set. Usually, a mesh-like partition can be more easily applied to create the warping, for example, by polygon mesh or non-linear (higher-order) warping on each mesh element.

Figs. 6 and 7 depict, respectively, a system for inserting a watermark into and extracting the water mark from the encrypted and compressed video stream, including warping and re-registration.

5 In Fig. 6, the original message  $B_a$ , obtained from a DVD, in this example, by the playback unit is encrypted by unit 202. This unit obfuscates the original message to help prevent insertion of a false but valid watermark message and the retrieval of a watermark message by any unauthorized party. Any one of various encryption algorithms can be used.

10 The encrypted message is applied to an error correction coder 204 that improves the ability to recover the message even the the presence of significant signal degradation and many bit errors by introducing redundant information. Since signal degradation may be severe, especially in the case of a concerted attempt to eradicate the message, strong error correction with a great deal of redundancy is preferred. Reed-Solomon coding combined with convolutional coding is preferred.

15 The error corrected message next is applied to CDMA encoder 206 that maps (transforms) a single message bit into many bits (a chip or spreading waveform), which dramatically increases the spectrum (bandwidth) of the signal representing the message. Consequently, the density of the power spectra of the signal is greatly reduced so that the signal is more easily hidden and less easily eradicated. Expressed less precisely, the signal is spread over a greater part of the content but is inserted at a lower strength which results in it being harder to notice and harder to  
20 remove without degrading most of the content. In the best mode, a table of spreading waveforms is maintained so that it is possible to use different waveforms for different bits that are inserted into the content.

Another (optional) encrypter 212 encrypts the CDMA bitstream. The output of encrypter 212 is supplied to a first watermark modulator 214 that converts each bit into a  
25 modification to the content to yield the watermarked content. For example, a few of the frequency components of a signal might be modified by a small random amount in order to represent a single bit. The content is compressed at this point.

30 Compression decoder 216 decompresses the content, if necessary. If the original content is compressed, it must be decompressed at some point in order to present it to the user. This decoder (e.g., an MPEG-2 decoder) is not part of the watermarking system, but is depicted in the block diagram because it interacts with the watermarking system.

Watermark modulator 218 converts each bit into a modification to the uncompressed content to yield the watermarked content ( $C_n$ ). The block represents an alternate or additional point at which a watermark can be introduced into the content.

Anti-tampering encoder 220 applies any one of a set of geometric transformations, as described previously, that may change over time to the uncompressed image or video in order to make the watermark more difficult to detect or remove.

The watermark extractor 250, shown in Fig. 7, first carries out channel compensation in unit 252, to compensate for the effects of content degradation resulting from, e.g., analog copying or an intentional attempt to remove the watermark. This compensation could be implemented, for example, as a filter that has a transfer function which is the inverse of the transfer function of the degradation.

This is followed by decoding of the mapping function in unit 254, to restore image alignment. Decoding reverses the effect of the anti-tampering warping encoder of a watermark inserter by applying a geometric transformation that is the inverse of the one used by the encoder.

If the content from which the watermark is to be extracted is compressed, it must be decompressed. Compression decoder 254 decompresses the content, if necessary.

Watermark demodulator 256 retrieves each bit embedded in the watermarked content by detecting the modification introduced by the modulator. Decryptor 258 decrypts the retrieved bit stream to reverse the effect of encryptor 212.

CDMA waveform generator 266 duplicates the function of CDMA waveform generator of the watermark inserter 200 by re-creating the spreading waveforms used in the inserter. CDMA decoder 260 inverts the effect of the CDMA encoder by mapping an entire spreading waveform back to a single bit. This mapping is accomplished by computing the correlation between the retrieved waveform and a waveform the possibly could have been used by the watermark inserter. The waveform with the largest correlation value is considered to be the correct one, that is, the one that was used by the inserter.

Error correcting decoder 262 corrects errors in the bits obtained from the CDMA decoder 260. If strong error correction with a large amount of redundancy is used, it is possible to recover the correct bits even in the presence of severe signal degradation. Decryptor 264

decrypts the retrieved bitstream to reverse the effect of decryptor 202. The resultant bitstream should be identical to the original bitstream.

Referring now to Fig. 3, in accordance with another aspect of the invention, watermark data, software, and other information content, may be downloaded from a service provider to the terminal by embedding the content in the analog channel of the video supplied by the provider. Conventionally, this type of information is supplied by downloading digitally, whereas the invention addresses environments in which the user does not have a digital link. Information may be supplied to the terminal over any medium, including the internet. The content being downloaded might include software, updates or modifications of terminal resident operating software, such as decryption keys, etc., without limitation. In accordance with the invention, the video signal, in the analog domain, such as NTSC, is encoded with data to be downloaded, in the active parts of the audio/video signal channel. By "active" part of the channel is meant the part of the channel that is visible to the user. By contrast, the non-active part of the channel is the part that is not visible, such as within the retrace or blanking interval, or the region of the image outside the screen viewing area.

The NTSC analog signal has a 6 MHz bandwidth channel within which this content to be downloaded to the user can be carried. The data may be embedded in the video in "message holes" as described in the copending application or in any other manner. Although the downloaded content will distort the image or audio perceived by the user, the period of distortion will be limited, and advantageously may be downloaded at a time when the user is not occupying the terminal, such as in the middle of the night. Even where the data is to be downloaded when the terminal is otherwise in use, the television or other equipment may be temporarily disabled or "blanked" or overlaid with a "downloading in process" message, to avoid confusing or annoying the user.

Although information has been downloaded in the past with the NTSC analog signal, only a very limited amount of data has been embedded into the non-active portion of the audio/video signal. However, the present invention capitalizes on the fact that the active region is many times greater in bandwidth capacity than the non-active portion of the channel.

Downloading per the invention is not limited to any particular standard, for example, PAM or other modulation format can be implemented. Furthermore, the downloaded content may be encrypted, compressed, etc.

Because the terminal may not have any handshaking capability with the content provider, the preferred embodiment implements local error checking, utilizing any suitable error checking algorithm. Error correction preferably also is implemented locally since there is no ability to request resending of error laden data.

5 Referring now to Fig. 8, in accord with another aspect of the invention, an improvement is made to the copending application in which a substantial amount of local storage is required for storing the reference CDMA waveform values for correlation with the waveforms received from and bearing watermark information associated with, the playback units. Fig. 8 of the  
10 copending application, and associated written disclosure, incorporated herein by reference, summarizes the CDMA encoding process, with column-by-column permutations of the waveform exclusive ORed with the bitstream to produce an output bitstream bearing the watermark content, in scrambled order. In accord with this invention, rather than storing the CDMA waveform values locally, the CDMA values are carried, column by column, in the running mark pack (RMG\_PCK), such as at the bottom of the pack, and building upward, as  
15 shown in Fig. 8. Alternatively, storage of the columns can be made serially downward in the pack, in a conventional way.

As an enhancement to this CDMA storage methodology, referring to Fig. 9, bits of different columns of the table can be selected to comprise a "single column" for exclusive OR bitwise processing.

20 Preferably, two columns of the CDMA waveform table are sent in each RMG\_PCK, although the number can be varied. An advantage of this methodology is in enhanced security, as the entire CDMA table is not available, in one location, for reverse engineering by a pirate. Furthermore, the described methodology provides enhanced flexibility, as different columns can be implemented for embedding in the RMG\_PCK, and are changeable.

25 Another aspect of the invention, shown in Fig. 10, is in an improvement to the RMG\_PCK data structure described in Fig. 14, and associated text, of the copending application. The layout of the structure comprises a running mark header, followed by a number of data, within an MPEG bitstream. In accord with this improvement, unused regions are reserved between the header and first data and between the successive data, that, together,  
30 conform to DVD specifications. The data structure hence is expandable, using the reserved areas, such that additional programming such as watermark, encryption, etc., can be added.

Copy protection watermarking cannot provide comprehensive protection of content. It only prevents the copying of content by a compliant recorder. There are numerous non-compliant recorders in the world, including all of the many millions of VCRs that have been sold to date, which will freely copy content containing a "never copy" watermark. For these non-compliant  
5 recorders, the Macrovision analog protection system (APS) may discourage casual copying on some machines, but many modern VCRs have no difficulty recording video signals containing APS and inexpensive devices that defeat APS are available to the public at the local electronics store. Furthermore, APS cannot protect the RGB video signals commonly used on computers or the digital video signals on, for instance, a USB or 1394 link. Additional protection can be  
10 afforded to content by using tracing watermarks, which do not prevent copying, but can be used to identify those who make illegal copies. Tracing watermarks are retrieved by a content provider or service provider and, consequently, a compliant recorder is not required to enable tracing. Consumer electronics devices do not need to detect these watermarks at all. Some consumer electronics devices, like the OPIMA terminal, would need to insert the tracing  
15 watermarks into content.

If one surveys current watermarking techniques, the idea of a consumer electronics device inserting watermarks into video in real-time appears impractical at first because of the complexity involved and the large amount of computation required. These techniques commonly perform video scene analysis, compute frequency transforms (e.g., the DCT, FFT, or  
20 wavelet transform) on large parts of the video, and invoke models of human perception. In addition, most techniques operate on uncompressed video whereas most consumer electronics devices receive compressed video (e.g., an MPEG bitstream). A few watermarking techniques operate on an MPEG bitstream by modifying the coefficients of the  $8 \times 8$  DCT blocks [3,4]. In this case, the VLCs (Huffman codes) are decoded, inverse quantization is performed to get the  
25 DCT coefficients, the DCT coefficients are modified to introduce the watermarks, the modified coefficients are quantized, and replacement VLCs are generated by Huffman encoding the DCT coefficients. The complexity and computation required to do all this in real-time is substantial. A more realistic alternative is to insert watermarks by replacing sections of the MPEG bitstream with alternate sections of bitstream.

30 Suppose that a watermark can be introduced into a video so that only some sections of the MPEG bitstream for the watermarked video are different from the bitstream for the unwatermarked video. For instance, if one bit of the watermark is represented by modifying the coefficients of a single  $8 \times 8$  DCT block and the number of bits comprising the watermark is

much less than the number of DCT blocks in the video, the watermarked and unwatermarked bitstreams would be the same except for those MPEG picture slices that contain a modified DCT block. For brevity and clarity in the discussion that follows, a section of the watermarked MPEG bitstream that differs from the unwatermarked bitstream will be referred to as a *message hole* (MH). (Fig. 16) In this example, the coefficients of the DCT block would be modified one way to embed a 0 bit into the watermarked bitstream and would be modified some other way to embed a 1 bit. In other words, for this message hole, there would be two alternative sections of bitstream; one represents a 0 and the other represents a 1. If both alternative sections of bitstream are available, either bit value (0 or 1) can be inserted into the message hole by inserting the appropriate section of bitstream. Any desired number of bits, any one of which can be 0 or 1, can be inserted into the watermarked bitstream this way so that a message (e.g., a tracing message containing a user ID) can be hidden in the video. All that is needed is a sufficient number of message holes and the alternative sections of bitstream for each one.

This approach to watermarking imposes a constraint: the alternative sections of bitstream associated with a message hole must be the same size (contain the same number of bits). Otherwise, the size of the overall bitstream would change depending on the message that was inserted. Decoder buffer underflows or overflows could occur. This constraint is satisfied by adaptively encoding or re-encoding the alternative portions of the video to obtain same-sized sections of bitstream. Recall the previous example, where the coefficients of a DCT block are modified to represent a bit. There would be two alternative bitstreams for the MPEG picture slice containing the block, depending on whether the bit is a 0 or a 1. One of these alternative slices can be encoded with different quantization levels until its size is as near as possible to the size of the other slice without being larger. Bit stuffing is then added to make the two slices exactly the same size. Either slice then can be inserted into the MPEG bitstream without affecting the decoder buffering.

The burden imposed on the OPIMA terminal (or similar device) can be reduced dramatically if much of the computation associated with watermarking is performed off-line before the MPEG bitstream is transmitted to the terminal. Everything, including watermarking and the adaptive encoding described in the preceding paragraph, can be done off-line except the final replacement of sections of bitstream with alternative sections of bitstream. To represent the tracing watermark message, the OPIMA terminal would need only to replace the appropriate sections of bitstream. This approach is simple and inexpensive to implement in the terminal, but requires that all the alternative sections of bitstream be transmitted to the terminal. These

sections of bitstream can be transmitted in some auxiliary data stream, such as a private data stream. If the amount of the bitstream that is replaced is small, the overhead is small. An advantage of this approach is that future improvements to the watermarking algorithms do not affect the terminal so long as the watermarks can be inserted by replacing sections of bitstream.

5       A variation on this technique attempts to reduce the overhead information that needs to be sent, but imposes a greater burden on the OPIMA terminal. In one example of such a tradeoff, the quantization level that keeps the same number of bits in a slice is computed off-line before the video is transmitted to the terminal. Instead of sending the alternative sections of bitstream via an auxiliary data stream, the alternative sections are created by the terminal using  
10   the quantization levels that were computed off-line. If needed, other information that describes how the alternative section of bitstream should be created can be computed off-line and sent to the terminal too. While the computational burden placed on the terminal is increased, the overhead associated with transmitting the quantization levels and other information describing how the alternative sections of bitstream are created should be less than the overhead of sending  
15   all the alternative sections of bitstream.

A packetized elementary stream (PES) of MPEG2 is composed by a sequence of PES packets, all of whose payloads consist of data from a single elementary stream, and all of which have the same stream\_id [6]. An elementary stream is a generic term for one of the coded video, coded audio or other coded bit streams. The problem of packet searching is to search for a  
20   particular packet along the bit stream, given the target packet's information. If each packet is associated with a unique, sequentially labeled packet number in its header, then the packet searching can be as simple as matching the unique packet number directly using a sequential search.

In general, however, the packet number may not exist in the header. One solution for that  
25   is to count the number of packets from the beginning of the stream until the current count matches with the target's packet number, assuming we know the i-th packet is our target. Obviously, this scheme is not robust because any packet loss between the beginning of the stream to the location of the target packet will cause picking up a wrong packet since the count becomes incorrect right after the packet loss. Another method to remedy the lack of packet  
30   number is to add the packet number into the header such as using the field of private data. The required bits for the packet numbers will increase the overhead. The insertion of packet numbers to packets is quite simple if it is performed during or before multiplexing of different MPEG streams to form the PES. However, for some situations, if only PES is available, a careful



examination of the buffer overflow problem is required because of the extra bits for packet numbers. A significant processing effort may be needed for de-multiplexing and multiplexing the PES, and buffer control. An alternative method for handling PES without packet number is to match packets using signatures which are composed from some information of packets. A signature should be a unique feature for one or more packets that there is no ambiguity in the matching process. There are many ways to create a signature. Obviously, if there is packet number in a packet, it can be used as a signature for matching. Three other approaches are described in the following.

One approach is to use the combination of stream\_id and presentation time-stamp (PTS) of a packet header [6]. The stream-id is an 8-bit field which specifies the type and number of the elementary streams and may take values in the range '1011 1100' to '1111 1111'. Since the first bit of stream-id is always '1', only last 7 bits are used for the signature. On the other hand, the PTS is a 33-bit number coded in three separate fields. It indicates the intended time of presentation in the system target decoder of the presentation unit that corresponds to the first access unit that commences in the packet. It is used to synchronize the presentation of multiple elementary streams, such as a coded video stream and the corresponding coded auditory streams. Since the PTS has a sequential order for each packet type along the PES, the searching of target packet can be stopped or reversed if it passes the target signature. Since all packet stream\_ids for an elementary stream are the same and different packets of different elementary streams may have the same PTS, a packet can not be specified uniquely by using either stream\_id or PTS. However, a combination of stream\_id and PTS can distinguish a specific packet.

Since PTS does not always exist in a packet header, not all the packets will have a signature in this case. To solve this problem, relative location can be used. In this scheme, an offset relative to a reference (absolute) location which has an unique signature is used to specify the target packet for matching. The search starts from matching the signature of the reference packet. Once it is found, we simply count the subsequent packets until the offset address is reached. For robustness, the offset should not be a big number, i.e. the distance between packet to be specified to the relative packet should not be far away. It implies that the number of bits to specify a relative location is, in general, smaller than that of absolute location and the overhead for packet locations is reduced. This is also true for that the packets have packet numbers.

A mismatch will happen for using relative relation to specify a packet when there is packet loss between the reference packet and the target packet. To solve this problem, multiple

reference packets can be used for cross-verification so that a mismatch can happen only when a packet loss exists between all reference location and the target location. In Figure 17,  $A, B$ , and  $C$  are potential reference packets. The target packet's location  $loc(t) = loc(A) + offset(A) = loc(B) + offset(B) = loc(C) + offset(C)$ . In this figure, 5  $offset(A) = +i$ ,  $offset(B) = +j$ , and  $offset(C) = -k$ . The target packet can be located using single or multiple reference packets. A packet loss before  $loc(A)$  or after  $loc(C)$  will not cause any mismatch during the search of target  $t$  in this example. A packet loss between  $loc(A)$  and  $loc(B)$  will cause a mismatch only if  $A$  is chosen as the only reference packet.

The second approach of creating a signature is to use lower-layer information within 10 compressed stream that is apparently unique and therefore does not cause ambiguity. Examples of such lower-layer information are frame number and time code. Though they seem convenient to use, the drawback of using lower-layer information is that the stream has to be decoded to the desired layer in order to extract such lower-layer. The computation is much higher than that for high-layer signatures such as using `stream_id` and PTS in the packet header.

15 The third approach of forming a signature is to use information of multiple packets. For example, a sequence of multiple `stream_id`'s from consecutive packets can form a signature. To search for the target packet based on the group of fields, a string matching algorithm (or elastic matching to cope with packet loss) can be used. The idea is illustrated in Figure 18 for using five `stream_ids`. The approach may save some signature overhead. For example, concatenating a 33-bit PTS with a 7-bit `stream_id` as a signature requires total 40 bits. (The first bit of `stream-id` is always 1 and therefore it can be skipped.) On the other hand, using five or fewer 7-bit `stream_ids` only requires 35 or less bits. See Fig. 18

25 Currently, this proposal focuses on using absolute and relative locations to specify packet locations. For absolute location, the approach of using packet numbers and that using `stream_id` with PTS are used for signature matching. For relative location, the offset to the previous closest absolute location is used. To avoid searching forever because of a packet loss or a signature miss, two absolute locations within a `OWM_PCK` are used and the packet searching process is refreshed if a new `OWM_PCK` is met.

30 An open watermark (OWM) stream is a packetized elementary stream which contains the data for replacing the compressed content stream (s) and the processing parameters. Its packets are called `OWM_PCKs`. They are encoded as a `private_stream_1`, i.e. the `stream_id` equals to "1011 1101b" as described in page 30 of MPEG-2 Part 1 specification. To distinguish other non-

watermark applications using private\_stream\_1, a sub\_stream\_id is introduced as the first PES\_packet\_data\_byte and its value for OWM equals to "1111 1111b".

A OWM\_PCK is stored physically before any content packets which contain message holes to be modified by that OWM\_PCK. A OWM\_PCK consists of a OWM\_header, multiple  
 5 OWM\_data and other watermark processing information. A OWM\_data is used for one replacement. Only one message hold is processed for one watermarking. The syntax of the OWM\_PCK, OWM\_data and other watermark stream information are described in tables 16-20. The OWM\_PCK header provides global information about watermark replacement algorithms and parameters used by all watermarkings within the OWM\_PCK. The num\_OWM\_data is the  
 10 total number watermarks in the OWM\_PCK. Each watermark uses one OWM\_data. The bit\_index points to the first bit to be sent for this OWM\_PCK in the bit array  $B_e$  which is the input of WM modulator in Figure 6. When a watermarking is finished, the bit\_index is update for the next watermarking according to the following formula.

$$\text{bit\_index} = \text{bit\_index} + \text{bit\_index\_incr.}$$

15 For a new OWM\_PCK, the bit\_index is used to resynchronize the bit to be sent. Let  $n_r$  be the number of bits to be sent for a watermarking, and Num\_replacements be the total number bitstreams in a OWM\_data to be used for replacing a message hole. If the first replacement is put into the MH of compressed content stream, the flag first\_replacement\_in\_MH equals to 1 and  $\text{Num\_replacements} = 2^{n_r} - 1$ , otherwise, the flag first\_replacement\_in\_MH equals to 0 and  
 20  $\text{Num\_replacements} = 2^{n_r}$ . Note that the number of replacement bitstreams for all OWM\_data in an OWM\_PCK do not change in order to reduce the overhead of the OWM\_data.

For a watermarking, the size of a message hole is determined by the MH\_size. If the size of all message holes in the OWM\_PCK do not change, the flag MH\_size\_flag in the OWM header is set to 0, and only one MH\_size exists in the OWM header. Otherwise, each OWM\_data  
 25 contains a MH\_size. The location of the message hole in a content packet is determined by its packet location and the MH\_location\_offset. As described earlier, the packet location is specified by either absolute location or relative location. The MH\_location\_offset specifies the number of bytes between the message hold and the first byte after the PES\_packet\_length field.

The first\_OWM\_data and the next\_OWM\_data\_offset are used to jump directly to the first and  
 30 next OWM\_data in a OWM\_PCK respectively. They are the offsets in bytes from the first byte after the PES\_packet\_length field to that OWM\_data. For the last OWM\_data, next\_OWM\_data\_offset is set to zero. Future data can be put at the end of each OWM\_data.

To have a better implementation for run-time processing of watermarking, a few columns of CDMA waveform table may be stored inside the OWM\_header. It also provides a way to support more flexible CDMA coding since the CDMA waveforms can be changed for different  
5 OWM\_PCKs. The flag CDMA\_columns\_flag controls whether or not there are CDMA columns.

There are many different methods for performing the watermarking replacements which are selected within the routine MH\_replacement\_method ( ). Among these methods, the routine simple\_replacement\_method( ) performs simple ways of replacing MH bits according to the  
10 variable Mode. For the case of Mode = 0, the MH bits are replaced by b[0]. For the cases of Mode = 1 or 2, a sendBit is formed by extracting  $n_r$  bits from input bit array which is an input of watermark modulator pointed by bit\_index. For the case of Mode = 1, the MH bits are replaced by b[sendbit-1] if the first replacement is in the MH. Otherwise, the MHs are replaced by b[sendbit]. For the case of version = 2, the  $n_r$  least significant bits of sendbit are reversed, e.g.  
15 "0000 0101" becomes "0000 0010" for  $n_r = 3$ . Then the MH bits are replaced by b[sendbit-1] if the first replacement is in the MH. Otherwise, the MHs are replaced by b[sendbit]. If the Mode value is not on the list, no replacement is performed. See Fig. 19.

Table 16

Syntax			No. of
bits	Mnemonic		
	OWM_PCK() {		
5	packet_start_code_prefix	24	bslbf
	stream_id	8	uimsbf
	PES_packet_length	16	uimsbf
	sub_stream_id	8	uimsbf
	if (sub_stream_id == '1111 1111') {		
10	new_OWM_system_header_flag		
	if ( new_OWM_system_header_flag == 1 )		
	OWM_system_header ( )		
	OWM_header ( );		
	for ( i = 0 ; i < num_OWM_data; i++ )		
15	OWM_data ( )		
	}		
	}		

20

Table 17

Syntax			No. of
bits	Mnemonic		
	OWM_system_header() {		
	<i>TBD</i>		
25	}		

Table 18

Syntax	No. of
bits Mnemonic	
5	<pre> OWM_header(){     bit_index     num_OWM_data     n<sub>r</sub>     first_replacement_in_MH_flag     NBits_packet_location_offset     NBits_MH_location_offset     NBits_bit_index_incr     first_OWM_data_offset     MH_size_flag     if (MH_size_flag == 0 )     MH_size     MH_replacement_method ( )     CDMA_columns_flag     if ( CDMA_columns_flag == 1 ){         num_CDMA_columns         for ( i = 0; i &lt; num_CDMA_columns; i++){             CDMA_column_incr             for ( j = 0; j &lt; NRows_CDMA; j++)                 CDMA_column_data         }     } } </pre>
10	
15	
20	
25	

Table 19

Syntax		No. of	
bits	Mnemonic		
	OWM_data( ) {		
5	next_OWM_data_offset		
	if (MH_size_flag == 1 )		
	MH_size		
	absolute_packet_location_flag		
	if (absolute_packet_location_flag == 1 )		
10	absolute_packet_location ( )		
	else		
	packet_location_offset		
	MH_location_offset		
	bit_index_incr	NBits_bit_index_incr	
15	tcimsbf		
	for ( i = 0; i < num_replacements; i++ ) {		
	for ( j = 0; j < MH_size; j++ )		
	replacement_bits[i][j]	8	bslbf
	}		
20	}		

Table 20

Syntax		No. of	
bits	Mnemonic		
	absolute_packet_location ( ) {		
5	if ( packet_type == MPEG2_PES ) {		
	stream_id[6..0]	8	bslbf
	PTS[32..0]	33	bslbf
	} else if ( packet_type == have_packet_numbers ) {		
	packet_num	32	bslbf
10	}		
	}		

**new\_OWM\_system\_header\_flag** : If new\_OWM\_system\_header\_flag = 1, new\_OWM\_system\_header is followed for updating OWM system parameters.

15 **bit\_index**: It points to the first bit to be sent for this OWM\_PCK in the bit array Be which is the input of OWM modulator 1 of Figure 6.

**num\_OWM\_data**: Number of WMs in this OWM\_PCK.

**n<sub>r</sub>**: Number of sending bits for a replacement.

20 **first\_replacement\_in\_MH\_flag**: If the first replacement is put in the MH of compressed content stream, this flag equals to 1. Otherwise, this flag equals to zero and all replacements are put in the OWM\_data.

**NBits\_packet\_location\_offset**: Number of bits for the parameter packet\_location\_offset.

**NBits\_MH\_location\_offset**: Number of bits for the parameter MH\_location\_offset.

**NBits\_bit\_index\_incr**: Number of bits for the parameter bit\_index\_incr.

25 **first\_OWM\_data\_offset**: Offset in bytes from the beginning of a OWM\_PCK to the first OWM\_data.

**MH\_size\_flag**: If the size of message holes within this OWM\_PCK may be different, then this flag equals to 1 and there are MH\_size data in the OWM\_data. Otherwise, this flag equals to 0 and MH\_size data is followed.

30 **MH\_replacement\_method ( )**: Different methods for replacing MH bits in MHs of this OWM\_PCK.

**CDMA\_columns\_flag**: If the CDMA columns are sent for CDMA process of WM bits in this OWM\_PCK, this flag equals to 1 and CDMA data are followed.



**num\_CDMA\_columns:** Number of CDMA columns.

**CDMA\_column\_incr:** The increment of column number respect to a reference column in CDMA table which is calculated from bit\_index.

**CDMA\_column\_data:** The CDMA column data.

5

---

```

Void simple_replacement_method(u6 Mode){
    u16 sendBit =0;
    locate MH bits of Message Hole using SectorNum and Offset;
    switch(Mode){
10  case 0: /* Replace MH bits with b[0] */
        replace MH bits with b[0];
        break;
        case 1: /* Replace MH bits with b[sendbit-1] */
            extract nr bits from Be[ ] pointed by bit_index and store them to
15  sendbit as in
            figure 6.5;
            if( first_replacement_in_MH){
                if(0< sendbit)
                    replace MH bits with b[sendbit-1];
20  } else {
                replace MH bits with b[sendbit];
            }
            break;
        case 2: /* Replace MH bits with b[reverse(sendbit)-1] */
25  extract nr bits from Be[ ] pointed by bit_index and store them to
        sendbit as in
            figure 6.5;
            reverse each one of nr least significant bits of sendbit;
            if( first_replacement_in_MH){
30  if(0< sendbit)
                replace MH bits with b[sendbit-1];
            } else {
                replace MH bits with b[sendbit];
            }
35  break;
        case OtherVersions:
            break;
    }
}
} A simple replacement method for a watermarking.

```

40

## References

1. I. J. Cox, J. Kilian, T. Leighton, and T. Shamoon, "A secure, robust watermark for multimedia," in *Proc. Workshop on Information Hiding*, Cambridge Univ., U.K., May 30 – June 1, 1996, pp. 185-206.
- 5 2. B. Schneier, *Applied Cryptography*, 2<sup>nd</sup> ed., New York: John Wiley & Sons, 1996.
3. F. Hartung and B. Girod, "Digital Watermarking of MPEG-2 coded video in the bitstream domain," in *Proc. ICASSP-97*, Munich, Germany, April 21-24, 1997.
4. F. Hartung and B. Girod, "Digital Watermarking of raw and compressed video," *Systems for Video Communication*, pp. 205-213, Oct. 1996.
- 10 5. M. D. Swanson, B. Zhu, and A. H. Tewfik, "Multiresolution scene-based video watermarking using perceptual models," *IEEE J. Select. Areas Commun.*, vol. 16, no. 4, pp. 540-550, May 1998.
6. ISO/IEC 13818-2, "Information technology -- Generic coding of moving pictures and associated audio information -- Part 2: Video," 1995.
- 15 7. J. Lubin, "A visual discrimination model for imaging system design and evaluation," David Sarnoff Research Center.
8. B. Girod, "The information theoretical significance of spatial and temporal masking in video signals," *Human Vision, Visual Processing, and Digital Display*, SPIE, vol. 1077, 1989.
- 20 9. A. B. Watson, "DCT quantization matrices visually optimized for individual images," NASA Ames Research Center.
10. C. I. Podilchuk and W. Zeng, "Image-adaptive watermarking using visual models," *IEEE J. Select. Areas Commun.*, vol. 16, no. 4, pp. 525-539, May 1998.
11. A. Ahumada and H. Peterson, "Luminance-model-based DCT quantization for color image compression," in *Human Vision, Visual Processing, and Digital Display*, SPIE, 1992.
- 25 12. J. D. Foley, A. Van Dam, S. K. Feiner, and J. F. Hughes. *Computer Graphics: Principles and Practice*, 2<sup>nd</sup> Ed., Reading, Ma.: Addison-Wesley, 1990.
13. W. Cai and J. Wang, "Adaptive multiresolution collocation methods for initial boundary value problems of nonlinear PDEs," *SIAM J. Numer. Anal.*, vol. 33, no. 3, pp. 937-970, June 30 1996.
14. Y.-T. Wu. *Image Registration Using Wavelet-Based Motion Model and Its Applications*. Ph.D. thesis, University of Pittsburgh, 1997.

15. M. Vetterli and J. Kovacevic. *Wavelet and Subband Coding*, Englewood Cliffs, NJ: Prentice Hall, 1995.
16. S. B. Wicker, *Error Control Systems for Digital Communication and Storage*, Englewood Cliffs, NJ: Prentice Hall, NJ 07458, 1995.
- 5 17. M. K. Simon, J. K. Omura, R. A. Scholtz, and B. K. Levitt, *Spread Spectrum Communications Handbook*, revised edition, McGraw-Hill, Inc., 1994.

**What is claimed is:**

1. A method for processing an audio or video data stream containing digital watermark data, comprising:

utilizing a playback unit for playing out information contained in the audio or video data stream; and

during playing by the playback unit, altering the audio or video information slightly by applying to the audio or video data stream a predetermined mapping function associated with the playback unit that is different from mapping functions associated with other playback units, to intentionally distort the audio or video content by a small amount not readily perceptible to a user;

such that audio or video information produced by combining multiple audio or video data streams corresponding to said information, from different playback units, will be perceptibly distorted.

2. The method in accordance with claim 1, configured such that the information comprises a video image embedded in a video data stream, and said video image is distorted slightly during playback by a playback unit in accord with the predetermined mapping function by an amount not readily visible to a viewer, but such that a video image produced by combining multiple video data streams reproduced by multiple different playback units is visibly distorted.

3. The method in accordance with claim 1 or 2, configured such that said mapping function changes with time during playback of the video image by a playback unit.

4. The method in accordance with claim 1 or 2, configured such that said mapping function is selected randomly from among a plurality of mapping functions pre-stored in a playback unit.

5. The method in accordance with claim 2, configured such that the image is distorted by the playback unit by compressing spacing between pixels in one direction and expanding spacing in another direction.

6. The method in accordance with claim 2, configured such that said mapping function is changed upon scene change of said video image.

7. The method in accordance with claim 6, configured such that the mapping function is changed in a first manner within a scene, and is changed in a second manner upon a scene change.

8. The method in accordance with claim 2, configured such that said mapping function is defined by a geometric transformation

10

9. The method in accordance with claim 8, configured such that said mapping function is derived by backward warping of a two-dimensional geometric transformation of said video image.

15 10. The method in accordance with claim 8, configured such that said mapping function is derived by a three-dimensional geometric transformation of said video image.

11. The method in accordance with claim 8, configured such that said mapping function is linear.

20

12. The method in accordance with claim 8, configured such that said mapping function is quadratic.

13. The method in accordance with claim 8, configured such that said mapping function is a spline function.

25

14. The method in accordance with claim 8, configured such that a motion vector is applied to one or more pixels of said video image for image transformation.

15. The method in accordance with claim 8, in which the mapping function is obtained from a stored table.

5        16. The method in accordance with claim 8, in which the mapping function is obtained from a computed table.

17. The method in accordance with claim 8, configured such that different image transformations are performed in different regions of said video image.

10

18. A video playback unit, comprising:

an input for receiving an encoded data stream bearing a video image;

a decoder for decoding the encoded video stream; and

15 means for imparting a prescribed transformation to the video image for intentionally warping the video image in a manner, and by an amount, not readily visible to a viewer such that a composite video image produced by multiple said video playback units will be visibly distorted.

19. A playback unit in accordance with claim 18, configured such that said warping  
20 changes with time during playback of the video image.

20. A playback unit in accordance with claim 18, configured such that said warping is selected randomly from among a plurality of mapping functions pre-stored in a playback unit.

25        21. A playback unit in accordance with claim 18, configured such that the image is warped by compressing spacing between pixels in one direction and expanding spacing in another direction.

22. A playback unit in accordance with claim 19, configured such that said warping changes upon scene change of said video image.

23. A playback unit in accordance with claim 18, configured such that said warping is  
5 defined by a geometric transformation

24. A playback unit in accordance with claim 18, configured such that said warping is derived by backward warping of a two-dimensional geometric transformation of said video image.  
10

25. A playback unit in accordance with claim 18, configured such that said warping is performed by a three-dimensional transformation of said video image.

26. A playback unit in accordance with claim 18, configured such that said warping is  
15 described by a linear function.

27. A playback unit in accordance with claim 18, configured such that said warping is described by a quadratic function.

28. A playback unit in accordance with claim 18, configured such that said warping is  
20 described by a spline function.

29. A playback unit in accordance with claim 18, including means for applying a motion vector to pixels of said video image for image transformation.  
25

30 A playback unit in accordance with claim 18, including means for performing different image transformations in different regions of said video image.

31. A method of downloading digital data or software from a content provider to a user terminal, comprising:

embedding the data or software into the active region of an analog channel of an audio or video signal transmission from the content provider to the user terminal.

5

32. The method in accordance with claim 31, in which the analog channel is a channel of a video signal transmission carrying analog information representing a video image.

33. The method in accordance with claim 32, wherein the video transmission is in NTSC or  
10 PAL format, and the active region of the analog channel of the transmission is outside a blanking interval.

34. The method in accordance with claim 32, including embedding the data or software into a region, or the entirety, of the video image.

15

35. The method in accordance with claim 31 or 32, including performing error checking at the user terminal.

36. The method in accordance with claim 35, including the further step of performing error  
20 correction at the user terminal.

37. The method in accordance with claim 32, including altering an image produced by a monitor at the user terminal so as to provide a prescribed display message or blanked monitor screen while said software or data are being downloaded from the content provider.

25

38. In a system for processing a digital data stream containing watermark data embedded in digital data stream packs, wherein the digital data stream is produced by any of a number of different playback units each characterized by a corresponding CDMA waveform, and the



digital data stream is CDMA encoded in accordance with the waveform of the playback unit from which the digital data stream is produced, a data processing method, comprising:

encoding the digital data by embedding digital data representing portions of the CDMA waveform in the digital data stream;

5 transmitting the encoded data; and

receiving and decoding the encoded data by retrieving embedded CDMA waveform portions and correlating retrieved CDMA waveform portions with the digital data stream.

39. The method in accordance with claim 38, wherein the embedded data includes data  
10 representing CDMA table columns.

40. The method in accordance with claim 39, wherein portions of different columns of a table are selected to comprise an equivalent single column for decoding.

15 41. The method in accordance with claim 38, wherein CDMA values are carried, in columns, by running mark packs within the digital data stream.

42. The method in accordance with claim 38, wherein storage of columns is made serially from the bottom of a pack upward.

20

43. The method in accordance with claim 39, wherein each pack carries two columns of a CDMA waveform.

25 44. A storage medium bearing an MPEG compatible data structure, the data structure being in the form of packs each comprising a header followed by successive data regions, at least some of which are separated by additional regions that are unused, and pointers for pointing from the header to a data region or pointing between data regions, in each case bypassing said unused region.

45. The storage medium in accordance with claim 4, including watermark data added to said unused regions of said data structure.

46. A method of searching for packets in an MPEG compatible data stream, comprising:  
5 deriving a packet signature from the stream identification (stream\_id) and presentation time stamp (PTS) as defined in an MPEG standard for packetized elemental streams (PES); and  
matching said packet signature as a reference packet with target packets in the data steam.

47. A method of searching for packets in an MPEG compatible data stream, of a type in  
10 which there is no presentation time-stamp (PTS) in a packet header, comprising:  
deriving a packet signature from a stream identification (stream\_id) of the data stream;  
obtaining an offset from an absolute location in the data stream having a signature; and  
counting packets by an amount of said offset from an address having said packet signature.

15 48. A method in accordance with claim 46, including implementing multiple reference packets for cross-verification of matches between said reference packet and target packets.

49. A method in accordance with claim 46, including implementing information obtained from multiple packets to form a packet signature

20

50. A method of searching for packets in an MPEG compatible data stream, comprising:  
deriving a unique packet signature from the MPEG data stream; and  
matching the packet signature as a reference packet with target packets in the MPEG data stream.

25

51. A method of searching for packets in an MPEG compatible data stream, comprising:  
counting packets from the beginning of the stream; and

identifying a target packet having a prescribed count.

52. A method of searching for packets in an MPEG compatible data stream, comprising:

adding packet numbers to packet headers within the data stream;

5 comparing packet header numbers with a prescribed header number from a field of private data; and

identifying a target packet having the prescribed packet header number.

53. In a system in which an MPEG video bitstream is sent from a content provider to a  
10 user terminal and tracing watermarks identifying the user terminal are inserted at the terminal into the MPEG bitstream by decompressing a portion of the bitstream and inserting the watermark into the decompressed video, a method of processing said MPEG encoded bitstream, comprising:

replacing a section of the MPEG bitstream by an auxiliary bitstream .

15

54. The system in accordance with claim 53, wherein said auxiliary bitstream comprises a private bitstream.

55. In a system in which an MPEG video bitstream is sent from a content provider to a user  
20 terminal and tracing watermarks identifying the user terminal are inserted at the terminal into the MPEG bitstream by decompressing a portion of the bitstream and inserting the watermark into the uncompressed video, a method of processing said MPEG encoded bitstream, comprising:

25 re-encoding said portion of the video to compensate for any change of said encoded bitstream length, wherein at least a portion of said re-encoding is performed by the content provider; and

placing said re-encoded portion of the video back into the MPEG bitstream.

56. In a system in which an MPEG video bitstream is sent from a content provider to a user terminal and tracing watermarks identifying the user terminal are inserted at the terminal

into the MPEG bitstream by decompressing a portion of the bitstream and inserting the watermark into the uncompressed video, in which computations must be performed on the bitstream for extracting the tracking watermarks therefrom, a method of processing the bitstream, comprising:

5

the content provider performing some of the computations;

sending information to the user terminal describing the computations performed by the content provider; and

10

the user terminal performing computations depending upon said information received from said content provider.

57. The method in accordance with claim 56, wherein said user terminal is programmed to perform on the bitstream processes selected from among a set of processes, and including the step of responding to said information received from said content provider by performing on the bitstream only those processes not already performed by said content provider.

58. A method of producing watermarks to be embedded within a bitstream of MPEG video frames, comprising:

20

producing attribute data specifying physical attributes of spatial domain watermarks;

encoding an auxiliary bitstream with said attribute data; and

25


using said encoded auxiliary bitstream to embed said spatial domain watermarks into said MPEG bitstream.

59. The method in accordance with claim 58, wherein said attribute data include size, shape and location of said spatial domain watermarks.

30


60. The method in accordance with claim 59, wherein said spatial domain watermark comprises a polygon-shaped modification of pixel values in an MPEG video frame.

61. The method in accordance with claim 60, in which said modification includes a function of replacement, addition, multiplication or exponentiation.




2/19

FIG. 2



3/19


FIG. 3






4/19

FIG. 4




5/19


FIG. 5



6/19


FIG. 6






8/19

FIG. 8




9/19

FIG. 9




10/19

FIG. 10



11/19


FIG. 11






12/19


FIG. 12




(a)



(b)




(c)



(d)

13/19


FIG. 13



(a)



(b)




(c)

01121110

(d)


14/19

FIG. 14




15/19

FIG. 15




16/19

FIG. 16

**Message holes in a video stream.**

17/19

FIG. 17



18/19

FIG. 18





FIG. 19





# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US99/19723

<b>A. CLASSIFICATION OF SUBJECT MATTER</b> IPC(6) : G06K 9/62 US CL : 382/159 According to International Patent Classification (IPC) or to both national classification and IPC		
<b>B. FIELDS SEARCHED</b> Minimum documentation searched (classification system followed by classification symbols) U.S. : 382/159 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Vetterli, Wavelets and subband coding, Hubbard, The World According to Wavelets, EIC search Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) Please See Extra Sheet.		
<b>C. DOCUMENTS CONSIDERED TO BE RELEVANT</b>		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 5,765,176 A [BLOOMBERG] 09 June 1998, abstract, col 6-8	1-56, 59-62
Y	US 5,465,308 A [HUTCHESON et al] 07 November 1995, abstract, col 8-18	1-56, 59-62
Y	Vetterli, Martin et al. Wavelets and Subband Coding, 1995, chapter 4-7	1-56, 59-62
Y	Hubbard. The World According to Wavelets, 1996, Chapter 4-5	1-56, 59-62
Y	Cox, I. et al. A Review of Watermarking and the Importance of Perceptual Modeling, Proc. of Electronics Imaging '97 February 97	1-56, 59-62
<input checked="" type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents:	*T*	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
*A* document defining the general state of the art which is not considered to be of particular relevance	*X*	document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
*B* earlier document published on or after the international filing date	*Y*	document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*&*	document member of the same patent family
*O* document referring to an oral disclosure, use, exhibition or other means		
*P* document published prior to the international filing date but later than the priority date claimed		
Date of the actual completion of the international search	Date of mailing of the international search report	
30 DECEMBER 1999	02 FEB 2000	
Name and mailing address of the ISA/US Commissioner of Patents and Trademarks Box PCT Washington, D.C. 20231	Authorized officer Gail Hayes      Joe Hill	
Facsimile No. (703) 305-3230	Telephone No. (703) 308-4562	

# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US99/19723

## C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	Koch, E et al Towards Robust and Hidden Image Copyright Labeling, Proc. of 1995 IEEE Workshop on Nonlinear Signal and Image Processing	1-56, 59-62
Y	US 5,574,787 A [RYAN] 12 November 1996, Abstract, col 4-12	1-56, 59-62

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US99/19723

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This international report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
  
2. ☒ Claims Nos.: 57 and 58  
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:  
  
Claim 57 is missing and claim 58 is dependent on claim 57.
  
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
  
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
  
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
  
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.  
☐ No protest accompanied the payment of additional search fees.

# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US99/19723

## B. FIELDS SEARCHED

Electronic data bases consulted (Name of data base and where practicable terms used):

Dialog, STN, West, IEEE proceedings

Image Recognition, Image Management, Image Identification and Classification, Watermarking, Image Format, video/audio copy protection (safeguard)